

Green'up™ Premium charging stations

equipment for wall mounting or fixing to the ground



0 590 52

Dimensions p. 378-379


Pack	Cat.Nos	Equipment for mounting charging stations on the wall or fixing to the ground
1	0 590 52	For plastic charging stations Pedestal for fixing plastic charging stations to the ground Option to integrate Plexo ³ boxes Cat.Nos 0 019 04/06/08(4 to 16 modules) for the protection devices
1	0 590 53	For metal charging stations Wall mounting kit with metal front cover
1	0 590 54	Pedestal for fixing metal charging stations to the ground Supplied with metal front cover Option to integrate protection devices on plates or rail chassis (dimensions equivalent to Atlantic box 600 x 400 mm)

Green'up™ Premium charging stations

communication options



Identification via RFID badge
0 590 59 + 0 590 56



0 767 11



Pack	Cat.Nos	Communication kit
1	0 590 56	For controlling functions embedded in the charging station and configuring the charging station remotely from a smartphone or PC via IP (RJ 45) or Wi-Fi Access control: for association with centralised readers Cat.No 0 767 04 or standalone readers via the Wiegand protocol IP communication For connecting the charging station to the installation's IP network and ensuring its compatibility with the following protocols: - OCPP 1.6, 2.0 - MODBUS RS 485 (one MODBUS address per single charging station and two MODBUS addresses per double charging station)
1	0 590 59	RFID reader RFID system (identification via RFID badge, integrated RFID encoder reader) available on metal charging stations with communication kit Cat.No 0 590 56 Supplied with 1 badge to be activated Additional badges to be ordered separately Cat.Nos 0 767 11/12/13 Can read the following formats : ISO 14443A, ISO 14443B, ISO 18092, ISO 15693
1	0 767 11	13.56 MHz badges for badge readers ISO format badges Dim. 50 x 80 mm 13.56 MHz Mifare contactless badge

Energy management multi-support
web servers p. 101

