

# Hotel equipment - user interfaces

BUS/SCS (continued)



# Hotel equipment

equipment for reception, room and infrastructure



0 487 76



0 487 70



348402

MH201

F458

Pack	Cat.Nos	Control indicators for room management
1	0 487 75	To be equipped with support frame Cat.No 0 487 79 <b>DO NOT DISTURB – MAKE UP ROOM external indicator and bell push-button</b> ● Black
1	0 487 76	<b>DO NOT DISTURB – MAKE UP ROOM external indicator and bell push-button + badge reader</b> ● Black
1	0 487 78	<b>Movement detector</b> PIR sensor for virtual key-card function To be installed in false ceiling Ø20 mm It detects guest presence and activates room functions
1	0 487 70	<b>Keycard switches BUS/SCS</b> DO NOT DISTURB – MAKE UP ROOM activation 2 modules To be equipped with support frame Cat.No 0 487 79 <b>Keycard reader with badge discrimination (guest or staff)</b> ● Black Enable launching of different actions depending on guest or staff incoming
1	0 487 71	<b>Keycard holder</b> Only works with ISO 13.56 MHz badges ● Black
1	0 487 79	<b>Accessories</b> <b>Support frame</b> For flush mounting in 2 and 3 modules flush-mounting boxes
1	0 487 88	<b>Flush mounting accessory</b> For extra-slim flush-mounting installation (e.g furniture) Replace use of support frame Cat.No 0 487 79

Pack	Cat.Nos	Reception products
5	0 675 89	<b>Badge - key card</b> Credit card shaped badge (ISO 50 x 80 mm) It uses transponder technology with frequency 13.56 MHz To be used with programmer Cat.No 348402 The badge can be customized and is sold in packs of 10
1	348402	<b>Programmer</b> Desk device to be connected to the PC (at the reception) to program badges
1	MH201	<b>Room products</b> <b>IP scenario module</b> Manages scenarios related to hotel rooms (With basic time and logic conditions) Works as a gateway for the Configuration software
1	0 484 08	<b>Bacnet Room Controller Units</b> Power modules equipped with output contacts for controlling: - different types of ON/OFF load (lighting, roller shutters, contactors, motors, etc.) - a DALI dimming output for 64 ballasts max. Loads are managed by the controls to which they are linked: either by BUS SCS controls, or by wired connection input terminals (switches, push-buttons, volt-free contacts)
1	0 484 12	8 inputs - 10 outputs 8 DIN modules 17.5 mm 16 inputs - 16 outputs 12 DIN modules 17.5 mm
1	F458	<b>Infrastructure products</b> To be associated with Cat.No MH201 <b>IP server</b> To be used in systems with over 100 rooms or zones (over 100 Cat.Nos 0 035 96 installed) 6 DIN modules 17.5 mm
1	F459	<b>Driver manager</b> Integration platform with other brand systems 6 DIN modules 17.5 mm Contact the agency to check the feasibility of specific integrations and to request the licence needed to use the Driver manager
1	3544SW	<b>Softwares</b> Software for the monitoring of the status of the room, for the corresponding basic management and the programming of badges For hotels with up to 20 rooms
1	3546SW	For hotels over 20 rooms