

Other chimes



0 416 50

Pack	Cat.Nos	Electromechanical chimes
1	0 416 50	<p>White Dim.: 116 x 116 x 48 mm Tone level: 80 dB at 1 m</p> <p>8-12 V ~ chime Compatible with non-illuminated push-button Cat.No 0 416 46 or illuminated push-buttons Cat.Nos 0 416 45/47 Use a 8 VA transformer Cat.No 4 130 91 or 0 420 25</p>
1	0 416 51	<p>127/230 V ~ chime 2 note chime - 50/60 Hz Compatible with illuminated push-button Cat.No 0 416 45</p>
1	0 416 52	<p>230 V ~ chime with transformer 50/60 Hz with built-in 8-12 V transformer Class II Compatible with non-illuminated push-button Cat.No 0 416 46 or illuminated push-buttons Cat.Nos 0 416 45/47</p>

Pack	Cat.Nos	Transformer - 230 V/12 V - 8 V																																				
10	0 420 25	<p>Conform to IEC 61 558-2-8 standard Protected against short-circuits and overvoltages Wall-mounting with screws</p> <table border="1"> <thead> <tr> <th colspan="3">Secondary tension (V)</th> <th colspan="3">Intensity (A)</th> <th colspan="3">Power (VA)</th> <th colspan="3">Dimensions (mm)</th> </tr> <tr> <th>Length</th> <th>Depth</th> <th>Height</th> <th>Length</th> <th>Depth</th> <th>Height</th> <th>Length</th> <th>Depth</th> <th>Height</th> <th>Length</th> <th>Depth</th> <th>Height</th> </tr> </thead> <tbody> <tr> <td>92</td> <td>56</td> <td>42</td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Secondary tension (V)			Intensity (A)			Power (VA)			Dimensions (mm)			Length	Depth	Height	Length	Depth	Height	Length	Depth	Height	Length	Depth	Height	92	56	42	1								
Secondary tension (V)			Intensity (A)			Power (VA)			Dimensions (mm)																													
Length	Depth	Height	Length	Depth	Height	Length	Depth	Height	Length	Depth	Height																											
92	56	42	1																																			

Bells, bell pushes



0 416 46



0 416 47



0 412 43

Pack	Cat.Nos	Bell pushes				
5	0 416 46	<p>Surface-mounting White Supplied without fixing screws</p> <p>24 V - 2 A bell push IP 30 - class III W Dim.: 50 x 25 x 20 mm</p>				
10	0 416 45	<p>230 V - 2 A bell push with illuminated label holder IP 30 - class II Supplied without lamp Dim.: 70 x 35 x 24 mm Use lamps Cat.No 0 898 26 - 12 V and Cat.No 0 898 21 - 220 V</p>				
10	0 416 47	<p>24 V - 2 A universal - bell push with label holder Weatherproof IP 44 (IK 07) - Class III W Dim.: 70 x 70 x 25 mm Illuminated with lamp Cat.No 0 898 26 Can be used with any type of chimes (electronic or electromechanical)</p>				
10	0 412 21	<p>Lido bells IP 20 - IK 04 Average acoustic output at 1 m: 80 dB at 1 m Surface-mounting with screws with levelling facilities</p> <p>Class II (double insulated)</p> <table border="1"> <thead> <tr> <th>Consumption (mA)</th> <th>Average acoustic output at 1 m in dB</th> </tr> </thead> <tbody> <tr> <td>30</td> <td>80</td> </tr> </tbody> </table>	Consumption (mA)	Average acoustic output at 1 m in dB	30	80
Consumption (mA)	Average acoustic output at 1 m in dB					
30	80					
1	0 412 43	<p>With built-in transformer 230 V ~ - 50/60 Hz Dim.: 135 x 88 x 48 mm Warning: take lamps out of the bell pushes</p>				

