

## Safety boxes 90 series

for fire detection & fire alarm system, emergency exit, extinguishing system, remote switching



1 380 69



1 380 23



1 380 73



1 380 74



1 380 25

Pack	Cat.Nos	Manual call points (MCP)																					
		<p><b>IP 30 - IK 07</b> Surface-mounting or flush-mounting (IP 30) Dimensions: 90x90x57 mm (surface-mounting with its base) or 90x90x24 mm (flush-mounting with flush boxes for wiring devices - drilling diameter 67 mm - for 60 mm fixing centres) Can be fitted on trunking Cat. Nos 0 104 63/64, 35x105 mm or 50x105 mm, with the universal support Cat. No 0 109 13 Call by pressing the membrane (pressure 2.5 kg) with clear display of the call position Reset on front of device, with special key Cat. No 0 380 38 (supplied with the product) Possibility to add an optional mechanical status indicator Cat. No 1 380 93 to provide additional signalling Can receive a sealable cover Cat.No 0 380 97</p> <p><b>MCP for fire detection and fire alarm systems</b> Conform to EN 54-11 standard CE-CPR approved Type A – simple action Color of the mechanical enclosure: red RAL 3000</p> <tr> <td>1</td> <td>1 380 69</td> <td>MCP - conventional - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=</td> </tr> <tr> <td>1</td> <td>1 380 68</td> <td>MCP - conventional - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)</td> </tr> <p><b>Devices for emergency exit (DCMIS)</b> Allow the immediate release of an exit door normally closed by an electromagnetic lock Color of the mechanical enclosure: green RAL 6016</p> <tr> <td>1</td> <td>1 380 23</td> <td>DCMIS - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=</td> </tr> <tr> <td>1</td> <td>1 380 48</td> <td>DCMIS - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger: a technical alarm a CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)</td> </tr> <p><b>Emergency shutdown control devices</b> Color of the mechanical enclosure: white RAL 9003</p> <tr> <td>1</td> <td>1 380 71</td> <td>Emergency shutdown control device - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=</td> </tr> <tr> <td>1</td> <td>1 380 73</td> <td>Emergency shutdown control device - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger a technical alarm</td> </tr> <tr> <td>1</td> <td>1 380 74</td> <td>Emergency shutdown control device - 2 contacts with indicator light Equipped with 2 NO/NC contacts - 5A - 24V= Equipped with 2 indicator lights (1 red LED + 1 green LED) 230 V free signalling wiring Can be used to trigger a technical alarm 2 LEDs in front indicating the change of status of the controlled equipment</td> </tr>	1	1 380 69	MCP - conventional - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=	1	1 380 68	MCP - conventional - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)	1	1 380 23	DCMIS - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=	1	1 380 48	DCMIS - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger: a technical alarm a CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)	1	1 380 71	Emergency shutdown control device - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=	1	1 380 73	Emergency shutdown control device - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger a technical alarm	1	1 380 74	Emergency shutdown control device - 2 contacts with indicator light Equipped with 2 NO/NC contacts - 5A - 24V= Equipped with 2 indicator lights (1 red LED + 1 green LED) 230 V free signalling wiring Can be used to trigger a technical alarm 2 LEDs in front indicating the change of status of the controlled equipment
1	1 380 69	MCP - conventional - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=																					
1	1 380 68	MCP - conventional - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)																					
1	1 380 23	DCMIS - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=																					
1	1 380 48	DCMIS - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger: a technical alarm a CCTV camera (visually and recording - allows remote viewing and recording of any malicious act)																					
1	1 380 71	Emergency shutdown control device - 1 contact Equipped with 1 NO/NC contact - 5A - 24V=																					
1	1 380 73	Emergency shutdown control device - 2 contacts Equipped with 2 NO/NC contacts - 5A - 24V= Second contact can be used to trigger a technical alarm																					
1	1 380 74	Emergency shutdown control device - 2 contacts with indicator light Equipped with 2 NO/NC contacts - 5A - 24V= Equipped with 2 indicator lights (1 red LED + 1 green LED) 230 V free signalling wiring Can be used to trigger a technical alarm 2 LEDs in front indicating the change of status of the controlled equipment																					

Pack	Cat.Nos	Manual call points (MCP) (continued)																		
		<p><b>Extinguishing system device</b> Color of the mechanical enclosure: yellow RAL 1032 Device for extinguishing system - 1 contact Equipped with 1 NO/NC contact - 5A - 24V= Equipped with a sealable cover (Cat.No 0 380 97)</p> <tr> <td>1</td> <td>1 380 25</td> <td></td> </tr> <p><b>Accessories</b></p> <tr> <td>1</td> <td>1 380 95</td> <td>Sealing kit Used to give IP 65 protection to Cat.Nos 1 380 23/25/71 Contains 3 pierceable membrane glands, 1 membrane, 1 seal, 1 frame, 2 sealing caps for fixing screws and 2 screws</td> </tr> <tr> <td>1</td> <td>1 380 93</td> <td>Mechanical status indicator Provides additional signalling Supplied with a sheet of labels customized for each application Compatible with devices Cat.Nos 1 380 69/68/23/25/48/71/73/74</td> </tr> <tr> <td>1</td> <td>1 380 94</td> <td>2-gang surface box Can receive 2 devices on a same base for a neat finish Horizontal or vertical mounting Color of the mechanical enclosure: white RAL 9003 Cable entries on each side and backside Dimensions : 200 x 90 x 33 mm Compatible with devices Cat.Nos N°1 380 69/68/23/25/48/71/73/74</td> </tr> <tr> <td>1</td> <td>0 380 97</td> <td>Sealable cover for manual call points To prevent accidental button presses Compatible with devices Cat.Nos 1 380 69/68/23/48/71/73/74</td> </tr> <tr> <td>1</td> <td>0 380 38</td> <td>Set of 10 special keys to reset ant to test devices Cat.Nos 1 380 69/68/23/25/48/71/73/74</td> </tr>	1	1 380 25		1	1 380 95	Sealing kit Used to give IP 65 protection to Cat.Nos 1 380 23/25/71 Contains 3 pierceable membrane glands, 1 membrane, 1 seal, 1 frame, 2 sealing caps for fixing screws and 2 screws	1	1 380 93	Mechanical status indicator Provides additional signalling Supplied with a sheet of labels customized for each application Compatible with devices Cat.Nos 1 380 69/68/23/25/48/71/73/74	1	1 380 94	2-gang surface box Can receive 2 devices on a same base for a neat finish Horizontal or vertical mounting Color of the mechanical enclosure: white RAL 9003 Cable entries on each side and backside Dimensions : 200 x 90 x 33 mm Compatible with devices Cat.Nos N°1 380 69/68/23/25/48/71/73/74	1	0 380 97	Sealable cover for manual call points To prevent accidental button presses Compatible with devices Cat.Nos 1 380 69/68/23/48/71/73/74	1	0 380 38	Set of 10 special keys to reset ant to test devices Cat.Nos 1 380 69/68/23/25/48/71/73/74
1	1 380 25																			
1	1 380 95	Sealing kit Used to give IP 65 protection to Cat.Nos 1 380 23/25/71 Contains 3 pierceable membrane glands, 1 membrane, 1 seal, 1 frame, 2 sealing caps for fixing screws and 2 screws																		
1	1 380 93	Mechanical status indicator Provides additional signalling Supplied with a sheet of labels customized for each application Compatible with devices Cat.Nos 1 380 69/68/23/25/48/71/73/74																		
1	1 380 94	2-gang surface box Can receive 2 devices on a same base for a neat finish Horizontal or vertical mounting Color of the mechanical enclosure: white RAL 9003 Cable entries on each side and backside Dimensions : 200 x 90 x 33 mm Compatible with devices Cat.Nos N°1 380 69/68/23/25/48/71/73/74																		
1	0 380 97	Sealable cover for manual call points To prevent accidental button presses Compatible with devices Cat.Nos 1 380 69/68/23/48/71/73/74																		
1	0 380 38	Set of 10 special keys to reset ant to test devices Cat.Nos 1 380 69/68/23/25/48/71/73/74																		

Stand-alone smoke alarm sensor  
p. 655



Old range / new range chart  
see e-catalogue

