

FR_711484

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE Product Multiple cord extension set Name and address of the applicant **LEGRAND FRANCE** 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE LEGRAND FRANCE Name and address of the manufacturer 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE Name and address of the factory NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD East Industrial Zone, Guanhaiwei Cixi City 315314 ZHEJIANG PROVINCE - CHINA Note: When more than one factory, please report on page 2 ☐ Additional Information on page 2 Ratings and principal characteristics See Annex Trademark / Brand (if any) legrand Customer's Testing Facility (CTF) Stage used Model / Type Ref. See Annex Additional information (if necessary may also be ☐ Additional Information on page 2 reported on page 2) A sample of the product was tested and found to IEC 60884-1:2002(ed.3) +A1:2006 +A2:2013 be in conformity with IEC 60884-2-7:2011 +A1:2013 ABND-ESH-P21020888-1 As shown in the Test Report Ref. No. which forms part of this Certificate ABND-ESH-P21020888-2

LCIE – Laboratoire Central des Industries Electriques 33, avenue du Général Leclerc – BP8 FR 92 266 Fontenay aux Roses Cedex www.lcie.fr

This CB Test Certificate is issued by the National Certification Body

Date: 28/05/2021





FR_711484

ANNEX

References, ratings and main characteristics:

| Model | Reference | Number of 16A socket-outlets | Number of 2,5A socket-outlets | Color of enclosure |
|--------|-----------|------------------------------|-------------------------------|--------------------|
| RNC10V | 0 493 99 | 4 | 4 | BLACK |

| standard Sheet: | Standard sheet V of CEE 7 (16A socket-outlet) / Standard sheet DIN 49440-2 (2,5A socket-out-let) / Standard sheet VII of CEE 7 (Plug) |
|---|---|
| rated current (A) | 16A |
| rated load (W) | 3680W |
| rated voltage (V) | 250V |
| household voltage (V) | 230V |
| degree of protection | IP20 |
| provision for earthing | with earthing contact (Solid earthing pin) |
| method of connecting the cable | Non-rewirable |
| type of terminals | - |
| type of connections | soldered / other (riveted) |
| colour | Black |
| socket-outlets | |
| multiple socket-outlets | 2,5A: 4 |
| number of socket-outlets | 16A: 4 |
| degree of protection against electric shock | normal protection |
| existence of shutters | with shutters |
| method of application - mounting | portable type |
| method of installation | - |
| plugs: | |
| class of equipment | I |
| entry of cable | lateral |

| t of | | Contification |
|------------------------|----------------|--|
| type of components | manufacturer | Certification |
| | Legrand France | NF 666578/M1 |
| Plug | | VDE 40018331 |
| | | CB FR 558589/M1 |
| Cable | Legrand France | VDE 40017697 |
| Built-in switch module | Legrand France | LCIE test report No.: ABND-ESH-P20072873 |
| SPD | Legrand France | LCIE test report No.: ABND-ESH-P20072863 |
| Socket-outlets | Legrand France | LCIE test report No.: ABND-ESH-P21020888-1 |



LCIE – Laboratoire Central des Industries Electriques 33, avenue du Général Leclerc – BP8 FR 92 266 Fontenay aux Roses Cedex www.lcie.fr

Date: 28/05/2021

