



Ref. Certif. No.

FR_725046

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Portable socket-outlet
Rewirable portable socket-outlets

Name and address of the applicant

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - France

Name and address of the manufacturer

LEGRAND FRANCE
128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY
87045 LIMOGES CEDEX - France

Name and address of the factory

NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD.
East Industrial Zone, Guanhaiwei Cixi City, 315314
Zhejiang Province - China

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark / Brand (if any)

legrand

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

See Annex

Additional information (if necessary may also be reported on page 2)

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60884-1:2022

As shown in the Test Report Ref. No. which forms part of this Certificate

ABND-ESH-P26062547

This CB Test Certificate is issued by the National Certification Body



LABORATOIRE CENTRAL DES INDUSTRIES ELECTRIQUES - LCIE
33 avenue du Général Leclerc
92260 Fontenay-aux-Roses, FRANCE
www.lcie.fr

Date: 28/07/2026

Signature: **Julien Gauthier**
Certification Officer



ANNEX

References, ratings and main characteristics:

Model	Type Reference	Number of socket-outlets	Color of enclosure
RNS10X	0 494 96	3	white/grey
	0 494 97	4	white/grey
	0 494 98	5	white/grey
	0 494 99	6	white/grey

Classification

standard Sheet:	Standard Sheet V of CEE 7
rated current (A) rated load (W) rated voltage (V) household voltage (V)	16A 3680W 250V 230V
degree of protection	IP20
provision for earthing	with earthing contact (with solid earthing pin or non-solid earthing pin)
method of connecting the cable	rewirable
type of terminals	screw-type
type of connections	-
colour	white/grey
socket-outlets	
multiple socket-outlets number of socket-outlets	16A : 3 to 6
degree of protection against electric shock	normal protection
existence of shutters	with shutters
method of application - mounting	portable type
method of installation	-



LABORATOIRE CENTRAL DES INDUSTRIES ELECTRIQUES - LCIE
33 avenue du Général Leclerc
92260 Fontenay-aux-Roses, FRANCE
www.lcie.fr

Date: 28/07/2026

Signature: Julien GAUTHIER
Certification Officer
