

AENOR

Confía

ENEC Certification Body registered under ID # 01. For further information, please consult www.enec.com

LICENCE

to use the European Mark



Licence Nr. ENEC/001150

Under the conditions given in the following pages of this document, the licence to use the ENEC Mark in conjunction with the suffix 01, as shown above, has been issued to:

LEGRAND GROUP ESPAÑA, S.L.
CL HIERRO, 56
28850 TORREJON DE ARDOZ (Madrid – España / Spain)

For the product(s):

LED luminaires for emergency lighting

Trade name(s):

LEGRAND

Complying with the following European Standards:

EN IEC 60598-1:2021; EN 60598-2-22:2014;
EN 60598-2-22:2014/A1:2020; EN 62262:2002

Date: 2023-09-08

Signature:

A handwritten signature in blue ink, appearing to read 'Rafael García', with a long horizontal stroke extending to the right.

Name: Rafael García
Position: Chief Executive Officer

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

AENOR INTERNACIONAL, S.A.U.
Cl Génova, 6
28004 MADRID (Spain)

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type of Product	LED LUMINAIRES FOR EMERGENCY LIGHTING
r1) Certificate n°	ENEC/001150
r2) Date of the Certificate	2023-09-08
r3) report n°	2023020067B1
r4) Name and address of the licensee	LEGRAND GROUP ESPAÑA, S.L. CL HIERRO, 56 28850 TORREJON DE ARDOZ (Madrid - España / Spain)
r5) Address of the factory	CL HIERRO, 56 28850 TORREJON DE ARDOZ (Madrid - España / Spain)
r6) European Standard	EN IEC 60598-1:2021; EN 60598-2-22:2014; EN 60598-2-22:2014/A1:2020; EN 62262:2002
r7) Type reference	See above for details
r8) Trade Mark	LEGRAND
r9) Rated voltage and frequency	See above for details
r10) N° lamps x rated power, type and lampholder	See above for details
r11) IP degree of protection	See above for details
r12) Power supply connection means	See above for details
r13) Classif. per holding surface material	See above for details
r14) Protection against electric shocks (class)	See above for details
r15) Rated lumen output and duration	See above for details
r16) Battery features	See above for details
r17) Additional information	See above for details
r18) General data	See above for details

Date of expiry: 2026-06-30

This certificate supersedes certificate 007/001150, dated 2023-07-24.

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
660600PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	50 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660601 PLE	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	70 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660601PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	70 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660602 PLE	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660602PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
660608 PLE	230 V~; 50/60 Hz	LED 4 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	2,4 V 1,5 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660608PL	230 V~; 50/60 Hz	LED 4 x 0,25 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	2,4 V 1,5 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660609 PLE	230 V~; 50/60 Hz	LED 4 x 2 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660609PL	230 V~; 50/60 Hz	LED 4 x 2 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660611PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 3 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
660612PL	230 V~; 50/60 Hz	LED 4 x 0,25 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 2 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660613PL	230 V~; 50/60 Hz	LED 4 x 2 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 2 h	4,8 V 2 Ah NiMH 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
660614PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	500 lm - 1 h	4,8 V 2 Ah NiMH 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus Autotest
661600PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	50 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661601 PLE	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	70 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
661601PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	70 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661602 PLE	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661602PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	2,4 V 0,8 Ah NiCd 2 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661603 PLE	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	2,4 V 1,5 Ah NiCd 2 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661603PL	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	2,4 V 1,5 Ah NiCd 2 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
661605PL	230 V~; 50/60 Hz	LED 4 x 0,25 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	160 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661606 PLE	230 V~; 50/60 Hz	LED 4 x 1 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661606PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661607 PLE	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661607PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
661608 PLE	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661608PL	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661609 PLE	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661609PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661610PL	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 3 h	4,8 V 2,0 Ah NiMH 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
661611PL	230 V~; 50/60 Hz	LED 2 x 0,25 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	90 lm - 3 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661612PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 2 h	4,8 V 2,0 Ah NiMH 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661614PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	500 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661615PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	500 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	Permanente / maintained, no permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus
661617PL	120 V~; 50/60 Hz	LED 4 x 0,25 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	160 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus 120 VAC

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
661618PL	120 V~; 50/60 Hz	LED 4 x 1 W	IP42; IK 07	Bornes/ terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	No permanente / non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus 120 VAC
662603PL	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 1 h	3,6 V 1,5 Ah NiCd 3 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus LVS2
662606PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 1 h	4,8 V 1,5 Ah NiCd 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus LVS2
662607PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 1 h	4,8 V 2,0 Ah NiMH 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus LVS2
662610PL	230 V~; 50/60 Hz	LED 4 x 0,5 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	100 lm - 3 h	4,8 V 2,0 Ah NiMH 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus LVS2

AENOR INTERNACIONAL S.A.U.

Génova, 6. 28004 Madrid. Spain

Tel. +34 91 432 60 00 - www.aenor.com Product certification body accredited by ENAC, number 1/C-PR275

CERTIFICATE OF THE ENEC EUROPEAN MARK

Type reference	Rated voltage and frequency	N° lamps x rated power, type and lampholder	IP degree of protection	Power supply connection means	Classif. per holding surface material	Protection against electric shocks (class)	Rated lumen output and duration	Battery features	Additional information	General data
662612PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	200 lm - 2 h	4,8 V 2,0 Ah NiMH 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus LVS2
662613PL	230 V~; 50/60 Hz	LED 4 x 1 W	IP 42; IK 07	Bornes / terminals	Apta para superficies normalmente inflamables / suitable for normally flammable surfaces	Clase / class II	350 lm - 2 h	4,8 V 2,0 Ah NiMH 4 elementos / cells	Permanente, posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest	Protección electrónica / electronic protection. URA-21 Plus LVS2