

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Socket-outlets for fixed installations

Name and address of the applicant

TCL-Legrand International Electrical(Huizhou) Co., Ltd
Bldg. B1-B3, East No.39 Hechang 6th Rd., HZZK Hi-tech
Industrial Development Zone, Huizhou, Guangdong - CHINA

Name and address of the manufacturer

TCL-Legrand International Electrical(Huizhou) Co., Ltd
Bldg. B1-B3, East No.39 Hechang 6th Rd., HZZK Hi-tech
Industrial Development Zone, Huizhou, Guangdong - CHINA

Name and address of the factory

TCL-Legrand International Electrical(Huizhou) Co., Ltd
Bldg. B1-B3, East No.39 Hechang 6th Rd., HZZK Hi-tech
Industrial Development Zone, Huizhou, Guangdong - CHINA*Note: When more than one factory, please report on page 2* [Additional Information on page 2](#)

Ratings and principal characteristics

See Annex

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

617650, 617750, 617850

Additional information (if necessary may also be reported on page 2)

/
 [Additional Information on page 2](#)

A sample of the product was tested and found to be in conformity with

IEC 60884-1:2002(ed.3) +A1:2006 +A2:2013


As shown in the Test Report Ref. No. which forms part of this Certificate

ARLI-19MY2823ACSHP

This CB Test Certificate is issued by the National Certification Body

LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 29/08/2019

Signature: **Didier BOURGES**
Manager of Certification Operations

ANNEX

RATING AND MAIN CHARACTERISTICS

Reference	Description	Color code of of enclosure
617650	1G BS 15A UNSWITCHED SOCKET WH	White
617750	1G BS 15A UNSWITCHED SOCKET AN	Anthracite
617850	1G BS 15A UNSWITCHED SOCKET CH	Ivory

standard Sheet:	BS 546
rated current (A)	15A
rated voltage (V)	250V
degree of protection	IP20
provision for earthing	with earthing contact
method of connecting the cable	rewirable
type of terminals	screw-type
colour	White, Anthracite, Ivory
socket-outlets	
multiple socket-outlets	15A: 1
number of socket-outlets	
degree of protection against electric shock	normal protection
existence of shutters	with shutters
method of application - mounting	flush-type
method of installation	design A



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 29/08/2019



Signature: **Didier BOURGIES**
Manager of Certification Operations