

Product Environmental Profile

Revolution Speedy µSP - Step Change AVR - Single Phase



PEP
ECO
PASS
PORT[®]



SMS'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

- Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

- Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

| | |
|--------------------------|---|
| Function | To protect the load of 300 Watts against from undervoltage, overvoltages, uncorrected voltage fluctuations, surges and spikes during 10 years. Product dimensions is 181x117x135: AxLxP (mm). Power factor= 1 |
| Reference Product |  |
| | Cat.No 0015970 |
| | Revolution Speedy - AVR - 300VA |

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers

• 0016520, 0015971, 0016620, 0016621

Product Environmental Profile

Revolution Speedy µSP - Step Change AVR - Single Phase



PEP
ECO
PASS
PORT[®]



CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market.

| | | | | |
|--|-------------------------------------|------------------------------|-----------------|---|
| Total weight of Reference Product | 2958 g (with unit packaging) | | | |
| Plastics as % of weight | 10.1% | Metals as % of weight | 0.2% | Other as % of weight |
| ABS | 10.1% | Copper alloys | 0.2% | PWB 75.4% |
| PVC | 0.8% | Steel | <0,1% | Electric cables 1.9% |
| | | | | Others electronics components 0.9% |
| | | | | |
| | | | | |
| | | | | Packaging as % of weight |
| | | | | paper 6.7% |
| | | | | wood 4.1% |
| Total plastics | 10.9% | Total metals | 0.2% | Total other and packaging 88.9% |

Estimated recycled material content: 5 % by mass.



MANUFACTURE

This Reference Product comes from a site that has initiated an environmental certification.



DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 2652 by road from our warehouse to the local point of distribution into the market Brazil.

Packaging is compliant with european directive 2004/12/EU concerning packaging and packaging waste. At their end of life, its recyclability rate is 98 % (in % of packaging weight).



INSTALLATION

For the installation of the product, only standard tools are needed.



USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

Product Environmental Profile

Revolution Speedy µSP - Step Change AVR - Single Phase



PEP
ECO
PASS
PORT[®]



■ END OF LIFE

The product end-of-life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. This product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• **Components to process specifically:**

In accordance with the requirements of this Directive, the following components must be removed and sent to specific channels for processing which comply with the WEEE Directive 2012/19/EU:

- PWB > 10cm² : 2232 g
- hazardous waste list*: 0 g

(*) Hazardous waste as defined by European Commission decision 2000/532/EU.

• **Extended producer responsibility:**

The sale of this product is subject to a contribution to eco-organisations in each country responsible for managing end-of-life products in the field of application of the European Waste Electronic and Electrical Equipment Directive.

• **Recyclability rate:**

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 67%. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 10 %
- metal materials (excluding packaging) : 0 %
- other materials (excluding packaging) : 46 %
- packaging (all types of materials) : 11 %



■ ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end-of-life. It is representative from products marketed and used in Brazil.

For each phase, the following modelling elements were taken in account:

| | |
|-----------------------------------|---|
| Manufacture | Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing. |
| Distribution | Transport between the last Group distribution centre and an average delivery point in the sales area. |
| Installation | The end of life of the packaging. |
| Use | <ul style="list-style-type: none">• Product category: active product.• Use scenario: in active phase of operation, with a power of 13W and associated time 30 %, in idle phase of operation with a power of 11W and 40% associated time, in sleep phase of operation with a power of 11W and 30% associated time and in off phase of operation with a power of 9W and 0% associated time of one year of operation. .• Energy model: Electricity Mix; Brazil - 2009. |
| End of life | The default end of life scenario maximizing the impacts. |
| Software and database used | EIME V5 and its database «CODDE-2015-04» |

Product Environmental Profile

Revolution Speedy µSP - Step Change AVR -
Single Phase



PEP
eco
PASS
PORT®



■ SELECTION OF ENVIRONMENTAL IMPACTS

| | Total for Life cycle | | Raw material and manufacture | | Distribution | | Installation | | Use | | End of life | |
|---|----------------------|--------------------------------------|------------------------------|------|--------------|------|--------------|------|----------|------|-------------|------|
| Global warming | 1.39E+02 | kg~CO ₂ eq. | 2.79E+01 | 20% | 6.69E-01 | < 1% | 1.83E-02 | < 1% | 1.10E+02 | 79% | 3.17E-01 | < 1% |
| Ozone depletion | 1.86E-05 | kg~CFC-11 eq. | 4.26E-06 | 23% | 4.74E-07 | 3% | 9.59E-11 | < 1% | 1.39E-05 | 75% | 8.09E-09 | < 1% |
| Acidification of soils and water | 1.14E-01 | kgSO ₂ eq. | 3.03E-02 | 26% | 1.80E-03 | 2% | 8.71E-05 | < 1% | 8.10E-02 | 71% | 1.21E-03 | 1% |
| Water eutrophication | 3.24E-02 | kg~PO ₄ ³⁻ eq. | 8.76E-03 | 27% | 4.83E-04 | 1% | 7.11E-05 | < 1% | 2.17E-02 | 67% | 1.38E-03 | 4% |
| Photochemical ozone formation | 2.93E-02 | kg~C ₂ H ₄ eq. | 7.22E-03 | 25% | 3.90E-05 | < 1% | 6.16E-06 | < 1% | 2.19E-02 | 75% | 9.42E-05 | < 1% |
| Depletion of abiotic resources - elements | 8.35E-03 | kgSb eq. | 8.34E-03 | 100% | 1.22E-10 | < 1% | 7.73E-10 | < 1% | 7.93E-06 | < 1% | 2.04E-08 | < 1% |
| Total use of primary energy | 4.28E+03 | MJ | 6.13E+02 | 14% | 8.47E+00 | < 1% | 2.60E-01 | < 1% | 3.66E+03 | 85% | 4.89E+00 | < 1% |
| Net use of fresh water | 3.62E-01 | m ³ | 2.11E-01 | 58% | 8.04E-04 | < 1% | 4.37E-06 | < 1% | 1.50E-01 | 41% | 2.79E-04 | < 1% |
| Depletion of abiotic resources - fossil fuels | 1.53E+03 | MJ | 4.20E+02 | 27% | 8.45E+00 | < 1% | 2.55E-01 | < 1% | 1.10E+03 | 72% | 4.52E+00 | < 1% |
| Water pollution | 6.90E+03 | m ³ | 2.18E+03 | 32% | 9.88E+01 | 1% | 2.88E+00 | < 1% | 4.58E+03 | 66% | 3.58E+01 | < 1% |
| Air pollution | 1.22E+04 | m ³ | 4.95E+03 | 40% | 2.35E+01 | < 1% | 1.80E+00 | < 1% | 7.22E+03 | 59% | 3.75E+01 | < 1% |

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

For products covered by the PEP other than the Reference product, the environmental impacts of each phase of the lifecycle are calculated with

To determine the environmental impact of a product covered by the PEP other than the cat.number, the following rules apply :

- Manufacturing, Distribution and End of Life phases are proportional to the mass of the product
- Utilisation phase is proportional to the electrical consumption

| | |
|---|--|
| Registration N°: LGRP-00244-V01.01-EN | Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by «PSR-0005-ed2-EN-2016 03 29» |
| Verifier accreditation N°: VH02 | Information and reference documents : www.pep-ecopassport.org |
| Date of issue: 09-2016 | Validity period: 5 years |
| Independent verification of the declaration and data, in compliance with ISO 14025:2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/> | |
| The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN) The elements of the present PEP cannot be compared with elements from another program Documents in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations» Environmental data in alignment with EN 15804 : 2012 + A1 : 2013 |  PEP eco PASS PORT ® |