

# Product Environmental Profile

## Cable LCS3 S/FTP U/UTP Category 5e



### LEGRAND'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

- Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

- Involve the environment in product design and provide informations in compliance with ISO 14025

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



### REFERENCE PRODUCT

<b>Function</b>	To transmit one communication signal on 1m according to Ethernet 100M - BP = 100 Mhz protocol, Cat 5e category, during 10 years and a 25% use rate in accordance with the standards in force ISO/IEC 14763-2 : 2019 and EN 50174-2 : 2018  Lifetime and use rate correspond to the application Building - LAN : Tertiary as defined in the table given in Appendix 6.1. of the specific rules for wire, cables and accessories.
<b>Reference Product</b>	
	<b>Cat.No</b> LG-032751 <b>LAN Cable - CAT5e F UTP - 4 Pairs - L 305 m - PVC</b>

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



### PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers
LG-032751 - LG-032750A - LG-032750 - LG-032751B - LG-032752 - LG-032752C - LG-032752A - LG-032753 - LG-032850 LG-032864 - LG-032865

# Product Environmental Profile

## Cable LCS3 S/FTP U/UTP Category 5e



### CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market.

<b>Total weight of Reference Product</b>	<b>0.03 kg (all packaging included)</b>		
<b>Product alone weight 0.03 kg</b>			

<b>Plastics as % of weight</b>		<b>Metals as % of weight</b>	<b>Other as % of weight</b>	
PC	<b>32.0 %</b>	Copper	<b>44.9 %</b>	
PE	<b>9.0 %</b>			

<b>Packaging (alone) : &lt;0.01 kg</b>				
PE	<b>0.5 %</b>		Cardboard	<b>7.7 %</b>
			Wood	<b>5.9 %</b>
			paper	<b>&lt;0.1 %</b>

<b>Total plastics : 0.01 kg</b>	<b>41.5 %</b>	<b>Total metals : 0.01 kg</b>	<b>44.9 %</b>	<b>Total others : &lt;0.01 kg</b>	<b>13.6 %</b>
---------------------------------	---------------	-------------------------------	---------------	-----------------------------------	---------------

At the date of edition of this document, the content of recycled material(s) is :

- Product alone (excluding packaging): 0% by mass
- Packaging only: 0% by mass



### MANUFACTURE

This Reference Product comes from site that have received ISO14001 certification.  
The final assembly site is located in China.



### DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 1477 km by planes and 1540.5 km by trucks and 64.4 km by boats from our warehouse to the local point of distribution into the market all around the world.



### INSTALLATION

For the installation of the product, only standard tools are needed.



### USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.



### END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.



### ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life.

The datasets collected in this PEP are representative of the year 2025.

For each phase, the following modelling elements were taken in account:

<b>System Limit</b>	<b>Manufacture A1-A3</b>	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
	<b>Distribution A4</b>	Transport between the last Group distribution centre and an average delivery point in the sales area.
	<b>Installation A5</b>	The end of life of the packaging.
	<b>Use B1-B7</b>	<ul style="list-style-type: none"><li>Product category: Communication and data wires and cables.</li><li>Use scenario: non-continuous operation for 10 years of working life, during 25% of the time (for building LAN tertiary applications) 0,924 mW/m of energy losses (determined by standard for 100M Ethernet Cat5e). This modelling duration does not constitute a minimum durability requirement.</li><li>Energy model: Consumption low voltage - Global - 2022.</li></ul>
	<b>End of life C1-C4</b>	The default end-of-life scenario for an international perimeter in accordance with the PCR-ed4-EN-2021 09 06.
	<b>D Module</b>	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and burdens beyond the boundaries of the system, and are not to be included in the life cycle totals.
	<b>Software and data-base used</b>	The set of indicators used is Indicators for PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0 EIME V6 and its CODDE-2025-04 database

Unless otherwise indicated the modelling energetic mix are those integrated in the data modules used from the aforesigned database.

# Product Environmental Profile

## Cable LCS3 S/FTP U/UTP Category 5e



### ENVIRONMENTAL IMPACTS

	Total Life Cycle		Manufacturing	Distribution	Installation	Use <sup>(1)</sup>			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Climate change - total	1.82E-01	kg CO2 eq.	1.07E-01	3.85E-02	8.18E-03	9.81E-03	0.00E+00	9.81E-03	1.85E-02	-1.95E-02
Climate change - fossil fuels	1.75E-01	kg CO2 eq.	1.07E-01	3.85E-02	1.59E-03	9.70E-03	0.00E+00	9.70E-03	1.84E-02	-1.78E-02
Climate change - biogenics	6.90E-03	kg CO2 eq.	6.13E-05	1.54E-05	6.59E-03	1.04E-04	0.00E+00	1.04E-04	1.25E-04	-1.69E-03
Climate change - land use and land use transformation	2.30E-08	kg CO2 eq.	1.41E-08	2.85E-09	4.12E-11	0.00E+00	0.00E+00	0.00E+00	6.01E-09	0.00E+00
Ozone depletion	2.39E-08	kg equivalent. CFC-11	2.27E-08	2.75E-11	5.68E-11	4.12E-11	0.00E+00	4.12E-11	1.10E-09	-5.58E-09
Acidification (AP)	3.71E-03	mole of H+ equiv	3.42E-03	1.20E-04	9.25E-06	5.03E-05	0.00E+00	5.03E-05	1.14E-04	-1.40E-03
Freshwater eutrophication	1.78E-06	kg P eq.	1.71E-06	1.15E-08	1.94E-09	1.51E-08	0.00E+00	1.51E-08	3.27E-08	-2.53E-08
Marine aquatic eutrophication	1.74E-04	kg of N equiv	1.02E-04	4.27E-05	2.22E-06	6.02E-06	0.00E+00	6.02E-06	2.11E-05	-2.09E-05
Terrestrial eutrophication	2.02E-03	mole of N equiv	1.17E-03	4.68E-04	2.97E-05	7.78E-05	0.00E+00	7.78E-05	2.76E-04	-2.45E-04
Photochemical ozone formation	7.39E-04	kg of NMVOC equiv	5.27E-04	1.22E-04	6.25E-06	1.97E-05	0.00E+00	1.97E-05	6.42E-05	-1.58E-04
Depletion of abiotic resources - elements	3.02E-05	kg.equivalent. Sb	3.02E-05	0*	0*	0*	0.00E+00	0*	3.55E-09	-1.37E-05
Depletion of abiotic resources - fossil fuels	3.40E+00	MJ	2.28E+00	5.43E-01	2.97E-02	2.07E-01	0.00E+00	2.07E-01	3.40E-01	-3.19E-01
Water requirement	2.89E-01	m3 of equiv. deprivation worldwide	2.85E-01	5.63E-04	9.32E-05	5.98E-04	0.00E+00	5.98E-04	2.82E-03	-6.87E-02
Emission of fine particles	2.21E-08	incidence of diseases	2.07E-08	2.44E-10	6.42E-11	3.50E-10	0.00E+00	3.50E-10	7.53E-10	-8.42E-09

\*Represents less than 0.01% of the total life cycle of the reference flow

<sup>(1)</sup> For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

# Product Environmental Profile

## Cable LCS3 S/FTP U/UTP Category 5e



	Total Life Cycle	Manufacturing	Distribution	Installation	Use <sup>(1)</sup>			End of Life	Module D	
					A1-A3	A4	A5	Total B1-B7	B2	B6
<b>Ionizing radiation, human health</b>	<b>9.26E-02</b>	<b>kBq of U235 equiv.</b>	7.66E-02	1.02E-04	6.08E-04	8.28E-03	0.00E+00	8.28E-03	7.02E-03	-2.44E-02
<b>Ecotoxicity (fresh water)</b>	<b>1.89E+00</b>	<b>CTUe</b>	1.34E+00	8.15E-02	3.94E-02	1.46E-02	0.00E+00	1.46E-02	4.11E-01	-3.25E-01
<b>Human toxicity, carcinogenic effects</b>	<b>2.23E-09</b>	<b>CTUh</b>	2.22E-09	1.01E-12	2.98E-13	1.18E-12	0.00E+00	1.18E-12	4.33E-12	-1.88E-10
<b>Human toxicity, non-carcinogenic effects</b>	<b>4.26E-08</b>	<b>CTUh</b>	4.24E-08	2.23E-11	1.17E-11	3.23E-11	0.00E+00	3.23E-11	2.06E-10	-1.90E-08
<b>Impacts related to land use/soil quality</b>	<b>2.94E-02</b>	-	2.82E-02	6.01E-04	3.56E-05	1.80E-04	0.00E+00	1.80E-04	3.75E-04	0.00E+00
<b>Use of renewable primary energy, excluding renewable primary energy resources used as raw materials</b>	<b>2.20E-01</b>	<b>MJ</b>	1.56E-01	7.47E-04	2.64E-03	3.36E-02	0.00E+00	3.36E-02	2.76E-02	-3.62E-02
<b>Use of renewable primary energy resources used as raw materials</b>	<b>1.07E-01</b>	<b>MJ</b>	1.07E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
<b>Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)</b>	<b>3.27E-01</b>	<b>MJ</b>	2.63E-01	7.47E-04	2.64E-03	3.36E-02	0.00E+00	3.36E-02	2.76E-02	-3.62E-02
<b>Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials</b>	<b>3.02E+00</b>	<b>MJ</b>	1.90E+00	5.43E-01	2.97E-02	2.07E-01	0.00E+00	2.07E-01	3.40E-01	-3.19E-01
<b>Use of non-renewable primary energy resources used as raw materials</b>	<b>3.81E-01</b>	<b>MJ</b>	3.81E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
<b>Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)</b>	<b>3.40E+00</b>	<b>MJ</b>	2.28E+00	5.43E-01	2.97E-02	2.07E-01	0.00E+00	2.07E-01	3.40E-01	-3.19E-01

\*Represents less than 0.01% of the total life cycle of the reference flow

<sup>(1)</sup> For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

# Product Environmental Profile

## Cable LCS3 S/FTP U/UTP Category 5e



	Total Life Cycle		Manufacturing	Distribution	Installation	Use <sup>(1)</sup>			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Use of secondary materials	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	6.74E-03	m <sup>3</sup>	6.63E-03	1.31E-05	2.14E-06	1.40E-05	0.00E+00	1.40E-05	7.96E-05	-1.60E-03
Hazardous waste disposed of	2.38E+00	kg	2.34E+00	0*	1.68E-03	0*	0.00E+00	0*	3.77E-02	-1.06E+00
Non-hazardous waste disposed of	2.32E-02	kg	1.24E-02	1.03E-03	2.15E-04	1.55E-03	0.00E+00	1.55E-03	8.09E-03	-1.46E-03
Radioactive waste disposed of	7.29E-06	kg	5.19E-06	6.21E-07	8.99E-08	3.09E-07	0.00E+00	3.09E-07	1.09E-06	-1.54E-06
Components for re-use	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	1.14E-02	kg	2.76E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	8.64E-03	0.00E+00
Materials for energy recovery	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	0.00E+00	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
<b>Total use of primary energy during the life cycle</b>	<b>3.73E+00</b>	<b>MJ</b>	<b>2.55E+00</b>	<b>5.44E-01</b>	<b>3.24E-02</b>	<b>2.40E-01</b>	<b>0.00E+00</b>	<b>2.40E-01</b>	<b>3.67E-01</b>	<b>-3.55E-01</b>

Biogenic carbon content of the product	0.00E+00	kg of C.	0.00E+00
Biogenic carbon content of the associated packaging	2.39E-03	kg of C.	2.39E-03

\*Represents less than 0.01% of the total life cycle of the reference flow.

<sup>(1)</sup> For the Use stage and in accordance with the PCR in force, information modules B1, B3, B4, B5 and B7, which all have indicator values equal to «0» (zero), are not represented in this table.

For biogenic carbon storage, the methodology used is -1/+1.

In accordance with current RCP rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column.

The values of the indicators defined in PCR-ed4-EN-2021 09 06 are available in digital format in the database on the pep-ecopassport.org website.

The life cycle analysis complies with the specific rules applicable to PSR-0001-ed4-2022 11 16, available at www.pep-ecopassport.org.

Digital service-related impacts of the product are not assessed (remote control).

# Product Environmental Profile

## Cable LCS3 S/FTP U/UTP Category 5e



To obtain the environmental impact values of products other than the Reference Product, take the environmental impact values of the Reference Product and multiply them by the values in the coefficient table below.

Associated references	Total life Cycle	Manufacturing	Distribution	Installation	Use	End of life
LG-032751	1.0	1.0	1.0	1.0	1.0	1.0
LG-032750A	1.1	1.1	1.1	1.0	1.0	1.1
LG-032750	1.1	1.1	1.1	1.0	1.0	1.1
LG-032751B	1.0	1.0	1.0	1.0	1.0	1.0
LG-032752	1.2	1.2	1.2	1.1	1.0	1.2
LG-032752C	1.2	1.2	1.2	1.1	1.0	1.2
LG-032752A	1.2	1.2	1.2	1.1	1.0	1.2
LG-032753	1.2	1.2	1.2	1.1	1.0	1.2
LG-032850	1.2	1.2	1.2	2.2	1.6	1.2
LG-032864	1.0	1.0	1.0	1.0	1.0	1.0
LG-032865	1.2	1.3	1.3	1.0	1.0	1.3

Registration number: <b>LGRP-00423-V04.01-EN</b>	Drafting rules: « <b>PEP-PCR-ed4-EN-2021 09 06</b> » <b>Supplemented by «PSR-0001-ed4-2022 11 16»</b>
Verifier accreditation N°: <b>VH02</b>	Information and reference documents: <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: <b>11-2025</b>	Validity period: <b>5 years</b>
<b>Independent verification of the declaration and data, in compliance with ISO 14025 : 2006</b>	
<input checked="" type="checkbox"/> Internal <input type="checkbox"/> External	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDomain)	
PEP are compliant with NF C08-100-1:2016 and EN 50693 :2019 or NF E38-500 :2022	
The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2006: «Environmental labels and declarations. Type III environmental declarations»	



Environmental data in alignment with EN 15804: 2012 + A2 : 2019