



Your usual Sales office www.legrand.com

Product Environmental Profile

Weatherproof bulkhead lights IP 44





■ LEGRAND'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites
- Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).
- Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations

• Involve the environment in product design and provide informations in compliance with ISO 14025

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



■ REFERENCE PRODUCT **■**

Function	Envelope for receiving an E27 lamp (60 W incandescent) to provide general lighting at 230 V for 20 years, inside and outside of the areas of traffic, tertiary and residential use. Impact resistance IK 06, tightness IP 44 and fire resistance 850 °C / 30 s.
Reference Product	Cat. No 0 604 92 Rully hood light = IR 64 = IK 06 = oval 60 W = F27 = plactic grid scrow fixing white
	Bulkhead light - IP 44 - IK 06 - oval 60 W -E27 - plastic grid screw fixing-white.

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



■ PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers

- 0 604 92
- 0 604 05





Product Environmental Profile



Weatherproof bulkhead lights IP 44



■ CONSTITUENT MATERIALS I

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU.

Total weight of	
Reference Product	474 g (all packaging included)

Plastics as % of weight		Metals as % of weight		Other as % of weight		
PP	13.2 %	Steel	2.1 %	Glass	55.3 %	
PC	4.9 %	Copper alloys	0.2 %	Ceramic	11.1 %	
PVC	1.0 %					
PS	0.2 %					
PE	0.1 %			Packaging as % of weight		
				Paper	7.7 %	
				Wood	4.1 %	
				PE	0.1 %	
Total plastics	19.4 %	Total metals	2.3 %	Total other and packaging	78.3 %	

Estimated recycled material content: 6 % by mass.



■ MANUFACTURE ■

This Reference Product comes from a site that observe the applicable legislation for industrial sites.



■ DISTRIBUTION **■**

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 780 km by road from our warehouse to the local point of distribution into the market in Europe. Packaging is compliant with european directive 2004/12/EU concerning packaging and packaging waste. At their end of life, its recyclability rate is 97 % (in % of packaging weight).



INSTALLATION ____

For the installation of the product, only standard tools are needed.



USE I

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.





Product Environmental Profile

Weatherproof bulkhead lights IP 44





■ END OF LIFE I

The product end-of-life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. This product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• Elements to process specifically:

In accordance with the requirements of this Directive, the following components must be removed and sent to specific channels for processing which comply with the WEEE Directive 2012/19/EU:

- plastic parts with brominated flame retardant: 87 g

• Extended producer responsability:

In France, the sale of products covered by the field of application of the European Directive on Waste Electronic and Electrical Equipment (WEEE) is subject to a contribution to a certified eco-organisation.

• Recyclability rate:

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 87 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

plastic materials (excluding packaging)
metal materials (excluding packaging)
other materials (excluding packaging)
packaging (all types of materials)
12 %



■ ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end-of-life. It is representative from products marketed and used in Europe, in compliance with the local current standards.

For each phase, the following modelling elements were taken in account:

Manufacture	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.					
Distribution	Transport between the last Group distribution centre and an average delivery point in the sales area.					
Installation	The end of life of the packaging.					
Use	 Product category: passive product. Use scenario: non-continuous operation for 20 years at 30 % of rated load, during 30 % of the time. This modelling duration does not constitute a minimum durability requirement. Energy model: Electricity Mix; Europe 27 - 2002. 					
End of life	The default end of life scenario maximizing the impacts.					
Software and database used	EIME V5 and its database «CODDE-2015-04»					



Your usual Sales office www.legrand.com

Product Environmental Profile







■ SELECTION OF ENVIRONMENTAL IMPACTS ■

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
Global warming	1.65E+00	kgCO ₂ eq.	1.58E+00	96 %	1.84E-02	1 %	3.27E-03	< 1 %	8.19E-04	< 1 %	4.93E-02	3 %
Ozone depletion	2.79E-07	kgCFC-11 eq.	2.77E-07	99 %	3.73E-11	< 1 %	1.88E-11	< 1 %	1.99E-10	< 1 %	1.25E-09	< 1 %
Acidification of soils and water	2.61E-03	kgSO ₂ eq.	2.32E-03	89 %	8.26E-05	3 %	1.56E-05	< 1 %	6.19E-06	< 1 %	1.88E-04	7 %
Water eutrophication	1.06E-03	kg(PO ₄)³- eq.	8.07E-04	76 %	1.90E-05	2 %	1.32E-05	1 %	2.32E-07	< 1 %	2.16E-04	20 %
Photochemical ozone formation	4.47E-04	kgC ₂ H ₄ eq.	4.25E-04	95 %	5.87E-06	1 %	1.10E-06	< 1 %	2.93E-07	< 1 %	1.47E-05	3 %
Depletion of abiotic resources - elements	4.01E-04	kgSb eq.	4.01E-04	100 %	7.36E-10	< 1 %	1.40E-10	< 1 %	3.73E-11	< 1 %	3.16E-09	< 1 %
Total use of primary energy	3.14E+01	МЛ	3.05E+01	97 %	2.47E-01	< 1 %	4.31E-02	< 1 %	1.41E-02	< 1 %	5.24E-01	2 %
Net use of fresh water	8.19E-03	m³	8.14E-03	99 %	1.65E-06	< 1 %	8.42E-07	< 1 %	2.14E-06	< 1 %	4.30E-05	< 1 %
Depletion of abiotic resources - fossil fuels	2.41E+01	МЈ	2.31E+01	96 %	2.58E-01	1 %	4.57E-02	< 1 %	8.43E-03	< 1 %	7.04E-01	3 %
Water pollution	2.34E+02	m³	2.24E+02	96 %	3.02E+00	1 %	5.13E-01	< 1 %	3.44E-02	< 1 %	5.59E+00	2 %
Air pollution	2.72E+02	m³	2.65E+02	97 %	7.54E-01	< 1 %	3.31E-01	< 1 %	3.51E-02	< 1 %	5.81E+00	2 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

Registration N°: LGRP-00521-V01.01-EN	Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by «PSR-0005-ed2-EN-2016 03 29»			
Verifier accreditation N°: VH23	Information and reference documents: www.pep-ecopassport.org			
Date of issue: 10-2017	Validity period: 5 years			
Independent verification of the declaration and data, in compliance w Internal ☑ External □				
The PCR review was conducted by a panel of experts chaired by Phili	ppe Osset (SOLINNEN)			
The elements of the present PEP cannot be compared with elements	from another program CO PASS			
Document in compliance with ISO 14025: 2010: «Environmental labels declarations»	s and declarations. Type III environmental PORT®			
Environmental data in alignment with EN 15804: 2012 + A1: 2013				