

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



LEGRAND'S ENVIRONMENTAL COMMITMENTS

- **Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

- **Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.


- **Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

Function	<p>To transmit one communication signal on 1m according to Ethernet 10G - BP = 500 MHz protocol, category 6A, during 10 years and a 25% use rate in accordance with the standards in force ISO/IEC 14763-2 : 2019 and EN 50174-2 : 2018</p> <p>Lifetime and use rate correspond to the application Building - LAN : Tertiary as defined in the table given in Appendix 6.1. of the specific rules for wire, cables and accessories.</p>
Reference Product	 <p>Cat.No LG-032878</p> <p>LAN Cable - CAT6A F/UTP - 2x4 Pairs - L 500 m - LSZH</p>

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers
LG-032878 - LG-032787 - LG-032787B - LG-032787N - LG-032798 - LG-032799 - LG-032828 - LG-032838 LG-032844 - LG-032845 - LG-032846 - LG-032868 - LG-032869 - LG-032778 LG-032883 - LG-032884 - LG-032887 LG-033855 - LG-032798B - LG-032799B - LG-032844B - LG-032845B

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market.

Total weight of Reference Product	0.16 kg (all packaging included)
--	---

Product alone weight 0.15 kg					
Plastics as % of weight		Metals as % of weight		Other as % of weight	
PE	21.4%	Copper and copper alloys	49.5%		
PP	17.7%	Aluminium	2.8%		
PET	2.2%	Steel	0.3%		
PA	<0,1%				

Packaging (alone) : 0.01 kg					
				Wood	5.3%
				Cardboard	0.8%
				paper	<0,1%

Total plastics : 0.07 kg	41.3 %	Total metals : 0.08 kg	52.6 %	Total others : 0.01 kg	6.1 %
---------------------------------	---------------	-------------------------------	---------------	-------------------------------	--------------



■ MANUFACTURE

This Reference Product comes from site that have received ISO14001 certification.
The final assembly site is located in China.



■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 3405.9 km by planes and 698.8 km by trucks and 694.4 by boats from our warehouse to the local point of distribution into the market all around the world.



■ INSTALLATION

For the installation of the product, only standard tools are needed.



■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.



■ END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life.

The datasets collected in this PEP are representative of the year 2025.

For each phase, the following modelling elements were taken in account:

System Limit	Manufacture A1-A3	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
	Distribution A4	Transport between the last Group distribution centre and an average delivery point in the sales area.
	Installation A5	The end of life of the packaging.
	Use B1-B7	<ul style="list-style-type: none"> Product category: Communication and data wires and cables. Use scenario: Use scenario: non-continuous operation for 10 years of working life, during 25% of the time (for building LAN tertiary applications) 2.728 mW/m (2x4 pairs) of energy losses (determined by standard for 10G Ethernet Cat6A). <p>This modelling duration does not constitute a minimum durability requirement.</p> <ul style="list-style-type: none"> Energy model: Consumption low voltage - Global - 2022.
	End of life C1-C4	The default end-of-life scenario for an international perimeter in accordance with the PCR-ed4-EN-2021 09 06.
D Module		Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and burdens beyond the boundaries of the system, and are not to be included in the life cycle totals.
Software and data-base used		The set of indicators used is Indicators for PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0 EIME V6 and its CODDE-2025-04 database

Unless otherwise indicated the modelling energetic mix are those integrated in the data modules used from the aforementioned database.

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



ENVIRONMENTAL IMPACTS

	Total Life Cycle		Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Climate change - total	1.21E+00	kg CO2 eq.	6.46E-01	4.19E-01	1.76E-02	2.90E-02	0.00E+00	2.90E-02	1.00E-01	-1.48E-01
Climate change - fossil fuels	1.18E+00	kg CO2 eq.	6.32E-01	4.19E-01	3.60E-03	2.86E-02	0.00E+00	2.86E-02	9.95E-02	-1.37E-01
Climate change - biogenics	2.88E-02	kg CO2 eq.	1.36E-02	1.74E-04	1.40E-02	3.06E-04	0.00E+00	3.06E-04	7.08E-04	-1.07E-02
Climate change - land use and land use transformation	1.11E-07	kg CO2 eq.	7.01E-08	6.36E-09	8.84E-11	0.00E+00	0.00E+00	0.00E+00	3.42E-08	0.00E+00
Ozone depletion	9.57E-08	kg.equivalent. CFC-11	8.95E-08	1.08E-10	1.20E-10	1.22E-10	0.00E+00	1.22E-10	5.93E-09	-3.65E-08
Acidification (AP)	2.16E-02	mole of H+ equiv	1.95E-02	1.34E-03	2.01E-05	1.49E-04	0.00E+00	1.49E-04	6.02E-04	-7.92E-03
Freshwater eutrophication	6.45E-06	kg P eq.	6.13E-06	6.51E-08	4.31E-09	4.47E-08	0.00E+00	4.47E-08	2.03E-07	-5.96E-07
Marine aquatic eutrophication	1.23E-03	kg of N equiv	6.15E-04	4.82E-04	4.76E-06	1.78E-05	0.00E+00	1.78E-05	1.07E-04	-1.42E-04
Terrestrial eutrophication	1.39E-02	mole of N equiv	6.89E-03	5.27E-03	6.37E-05	2.30E-04	0.00E+00	2.30E-04	1.40E-03	-1.65E-03
Photochemical ozone formation	4.97E-03	kg of NMVOC equiv	3.20E-03	1.37E-03	1.35E-05	5.82E-05	0.00E+00	5.82E-05	3.30E-04	-9.69E-04
Depletion of abiotic resources - elements	1.64E-04	kg.equivalent. Sb	1.64E-04	0*	0*	0*	0.00E+00	0*	1.99E-08	-7.45E-05
Depletion of abiotic resources - fossil fuels	2.26E+01	MJ	1.42E+01	5.85E+00	6.73E-02	6.11E-01	0.00E+00	6.11E-01	1.85E+00	-2.83E+00
Water requirement	1.38E+00	m3 of equiv. deprivation worldwide	1.35E+00	5.76E-03	2.06E-04	1.77E-03	0.00E+00	1.77E-03	1.63E-02	-3.88E-01
Emission of fine particles	1.27E-07	incidence of diseases	1.19E-07	2.55E-09	1.40E-10	1.03E-09	0.00E+00	1.03E-09	4.00E-09	-4.83E-08

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



Total Life Cycle			Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Ionizing radiation, human health	4.80E-01	kBq of U235 equiv.	4.14E-01	5.64E-04	1.39E-03	2.44E-02	0.00E+00	2.44E-02	4.03E-02	-1.53E-01
Ecotoxicity (fresh water)	9.22E+00	CTUe	6.58E+00	4.35E-01	8.30E-02	4.31E-02	0.00E+00	4.31E-02	2.08E+00	-2.02E+00
Human toxicity, carcinogenic effects	3.13E-09	CTUh	3.09E-09	8.18E-12	6.44E-13	3.50E-12	0.00E+00	3.50E-12	2.28E-11	-1.04E-09
Human toxicity, non-carcinogenic effects	2.30E-07	CTUh	2.29E-07	1.84E-10	2.47E-11	9.55E-11	0.00E+00	9.55E-11	1.09E-09	-1.03E-07
Impacts related to land use/soil quality	7.04E-02	-	6.10E-02	6.75E-03	8.14E-05	5.31E-04	0.00E+00	5.31E-04	2.06E-03	-2.48E-03
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	1.14E+00	MJ	8.65E-01	7.52E-03	6.05E-03	9.92E-02	0.00E+00	9.92E-02	1.59E-01	-2.29E-01
Use of renewable primary energy resources used as raw materials	3.01E-01	MJ	3.01E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	1.44E+00	MJ	1.17E+00	7.52E-03	6.05E-03	9.92E-02	0.00E+00	9.92E-02	1.59E-01	-2.29E-01
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	1.97E+01	MJ	1.13E+01	5.85E+00	6.73E-02	6.11E-01	0.00E+00	6.11E-01	1.85E+00	-2.59E+00
Use of non-renewable primary energy resources used as raw materials	2.88E+00	MJ	2.88E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-2.40E-01
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	2.26E+01	MJ	1.42E+01	5.85E+00	6.73E-02	6.11E-01	0.00E+00	6.11E-01	1.85E+00	-2.83E+00

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



Total Life Cycle			Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Use of secondary materials	8.06E-07	kg	8.06E-07	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	3.22E-02	m ³	3.15E-02	1.34E-04	4.73E-06	4.12E-05	0.00E+00	4.12E-05	4.59E-04	-9.02E-03
Hazardous waste disposed of	1.29E+01	kg	1.27E+01	0*	3.61E-03	0*	0.00E+00	0*	2.00E-01	-5.76E+00
Non-hazardous waste disposed of	3.01E-01	kg	2.41E-01	1.01E-02	4.83E-04	4.58E-03	0.00E+00	4.58E-03	4.49E-02	-8.59E-02
Radioactive waste disposed of	1.72E-04	kg	1.60E-04	5.79E-06	2.03E-07	9.11E-07	0.00E+00	9.11E-07	5.85E-06	-7.10E-05
Components for re-use	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	7.29E-02	kg	1.68E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.60E-02	0.00E+00
Materials for energy recovery	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	0.00E+00	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of primary energy during the life cycle	2.40E+01	MJ	1.54E+01	5.86E+00	7.34E-02	7.10E-01	0.00E+00	7.10E-01	2.01E+00	-3.05E+00

Biogenic carbon content of the product	0.00E+00	kg of C.	0.00E+00
Biogenic carbon content of the associated packaging	6.73E-03	kg of C.	6.73E-03

*Represents less than 0.01% of the total life cycle of the reference flow.

⁽¹⁾ For the Use stage and in accordance with the PCR in force, information modules B1, B3, B4, B5 and B7, which all have indicator values equal to «0» (zero), are not represented in this table.

For biogenic carbon storage, the methodology used is -1/+1.

In accordance with current RCP rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column.

The values of the indicators defined in PCR-ed4-EN-2021 09 06 are available in digital format in the database on the pep-ecopassport.org website.

The life cycle analysis complies with the specific rules applicable to PSR-0001-ed4-2022 11 16, available at www.pep-ecopassport.org.

Digital service-related impacts of the product are not assessed (remote control).

Product Environmental Profile

Cable LCS3 S/FTP F/FTP U/UTP Category 6A



To obtain the environmental impact values of products other than the Reference Product, take the environmental impact values of the Reference Product and multiply them by the values in the coefficient table below.

Associated references	Total life Cycle	Manufacturing	Distribution	Installation	Use	End of life
LG-032878	1.0	1.0	1.0	1.0	1.0	1.0
LG-032787	0.6	0.6	0.6	1.0	0.5	0.6
LG-032787B	0.6	0.6	0.6	1.0	0.5	0.6
LG-032787N	0.6	0.6	0.6	1.0	0.5	0.6
LG-032798	1.0	1.0	1.0	1.5	1.0	1.0
LG-032799	0.5	0.5	0.5	0.3	0.5	0.5
LG-032828	0.6	0.6	0.6	0.5	0.5	0.6
LG-032838	0.6	0.6	0.6	0.5	0.5	0.6
LG-032844	0.5	0.5	0.5	0.3	0.5	0.5
LG-032845	0.9	0.9	0.9	1.0	0.5	0.9
LG-032846	0.5	0.5	0.5	0.5	0.5	0.5
LG-032868	0.6	0.6	0.6	0.3	0.5	0.6
LG-032869	0.6	0.6	0.6	0.5	0.5	0.6
LG-032778	0.6	0.6	0.6	0.5	0.5	0.6
LG-032883	0.6	0.6	0.6	0.3	0.5	0.6
LG-032884	0.6	0.6	0.6	0.3	0.5	0.6
LG-032887	0.6	0.6	0.6	0.5	0.5	0.6
LG-033855	0.4	0.4	0.4	0.3	0.5	0.4
LG-032798B	1.0	1.0	1.0	1.5	1.0	1.0
LG-032799B	0.5	0.5	0.5	0.3	0.5	0.5
LG-032844B	0.5	0.5	0.5	0.3	0.5	0.5
LG-032845B	0.9	0.9	0.9	1.0	0.5	0.9

Registration number: LGRP-01411-V03.01-EN	Drafting rules: « PEP-PCR-ed4-EN-2021 09 06 » Supplemented by «PSR-0001-ed4-2022 11 16»
Verifier accreditation N°: VH02	Information and reference documents: www.pep-ecopassport.org
Date of issue: 11-2025	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2006	
Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)	
PEP are compliant with NF C08-100-1 :2016 and EN 50693 :2019 or NF E38-500 :2022 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2006: «Environmental labels and declarations. Type III environmental declarations»	



Environmental data in alignment with EN 15804: 2012 + A2 : 2019