

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



LEGRAND'S ENVIRONMENTAL COMMITMENTS

- **Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

- **Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

- **Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

Function	Protect, link by a connection point for 10 years with a 25% use rate for an application LAN: Tertiary.		
Reference Product			
	Cat.No AC4300MW1	Cat.No AC1100MW	Cat.No A1402
	1 Module RJ45 CAT5E UTP Socket Matt White	Plate - French/German std - square - 1 module - White	Support frame Arteor For German French

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

Module	Plate	Support
• AC4300MW1 • AC4300MT1 • AC4300MB1 • AC4307MT1 • AC4307MT4 • AC4307MB1 • AC4307MB4 • AC4307MW1 • AC4307MW4	• AC1100MW1 • AC1100MT1 • AC1100MB1 • AC1102MW1 • AC1102MT1 • AC1102MB1	• A1402

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market.

Total weight of Reference Product	0.18 kg (all packaging included)
--	---

Product alone weight 0.07 kg					
Plastics as % of weight		Metals as % of weight		Other as % of weight	
PC	19.7%	Steel	10.8%	Electronic card < 10cm ²	0.5%
PP	5.0%	Copper and copper alloys	0.4%		
PBT	0.3%	Gold	<0.1%		
PA	0.3%				
PS	<0.1%				

Packaging (alone) : 0.11 kg					
PP	28.5%			Cardboard	18.2%
PET	0.5%			Wood	14.7%
PE	0.1%			Paper	1.0%

Total plastics : 0.05 kg	54.4 %	Total metals : 0.02 kg	11.2 %	Total others : 0.11 kg	34.4 %
---------------------------------	---------------	-------------------------------	---------------	-------------------------------	---------------

At the date of edition of this document, the content of recycled material(s) is :

- Product alone (excluding packaging): 22% by mass
- Packaging only: 36% by mass



■ MANUFACTURE

This Reference Product comes from a site that has received ISO14001 certification.
The final assembly site is located in France.



■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 19000 km by boat and 1000 km by lorry from our warehouse to the local point of distribution into the market all around the world.



■ INSTALLATION

For the installation of the product, only standard tools are needed.



■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life. It is representative from worldwide marketed products.
The datasets collected in this PEP are representative of the year 2025.

For each phase, the following modelling elements were taken in account:

System Limit	Manufacture A1-A3	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
	Distribution A4	Transport between the last Group distribution centre and an average delivery point in the sales area.
	Installation A5	The end of life of the packaging.
	Use B1-B7	- Product category: PSR-0005-ed3.1-EN-2023 12 08 - §3.11 Copper telecom accessories. - Use scenario : non-continuous operation for 10 years, during 25% of the time. This modelling duration does not constitute a minimum durability requirement. - Energy model: Electricity Mix; production mix; Low voltage ; Global, GLO.
	End of life C1-C4	Choice of end-of-life by default model for PCR-ed4-EN-2021 09 06.
D Module		Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and burdens beyond the boundaries of the system, and are not to be included in the life cycle totals.
Software and data-base used		The set of indicators used is Indicators for PEF EF 3.1 (compliant: PEP ed.4, EN15804+A2) v2.0 EIME V6 and its database 2025-04-15.

Unless otherwise indicated the modelling energetic mix are those integrated in the data modules used from the aforementioned database.

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



ENVIRONMENTAL IMPACTS

	Total Life Cycle		Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Climate change - total	4.98E-01	kg CO2 eq.	2.89E-01	1.62E-02	1.33E-01	1.51E-02	0*	1.51E-02	4.46E-02	3.69E-03
Climate change - fossil fuels	4.87E-01	kg CO2 eq.	3.70E-01	1.62E-02	4.14E-02	1.50E-02	0*	1.50E-02	4.44E-02	4.14E-02
Climate change - biogenics	1.10E-02	kg CO2 eq.	-8.06E-02	0*	9.12E-02	1.60E-04	0*	1.60E-04	2.36E-04	-3.77E-02
Climate change - land use and land use transformation	4.30E-05	kg CO2 eq.	4.29E-05	1.03E-08	0*	0*	0*	0*	1.22E-08	8.68E-06
Ozone depletion	1.63E-08	kg.equivalent. CFC-11	1.18E-08	9.46E-11	1.83E-09	6.35E-11	0*	6.35E-11	2.52E-09	1.81E-09
Acidification (AP)	2.40E-03	mole of H+ equiv	1.52E-03	2.43E-04	2.76E-04	7.76E-05	0*	7.76E-05	2.75E-04	1.60E-04
Freshwater eutrophication	4.40E-06	kg P eq.	4.22E-06	4.15E-08	4.84E-08	2.33E-08	0*	2.33E-08	6.97E-08	1.21E-06
Marine aquatic eutrophication	4.86E-04	kg of N equiv	2.91E-04	6.65E-05	6.81E-05	9.28E-06	0*	9.28E-06	5.12E-05	5.87E-05
Terrestrial eutrophication	5.66E-03	mole of N equiv	3.24E-03	7.29E-04	9.11E-04	1.20E-04	0*	1.20E-04	6.60E-04	4.95E-04
Photochemical ozone formation	1.70E-03	kg of NMVOC equiv	1.14E-03	1.84E-04	1.90E-04	3.04E-05	0*	3.04E-05	1.56E-04	1.40E-04
Depletion of abiotic resources - elements	5.74E-05	kg.equivalent. Sb	5.74E-05	0*	6.31E-09	0*	0*	0*	7.16E-09	-1.53E-05
Depletion of abiotic resources - fossil fuels	1.58E+01	MJ	1.37E+01	2.46E-01	7.69E-01	3.19E-01	0*	3.19E-01	7.66E-01	-8.73E-01
Water requirement	1.70E-01	m3 of equiv. deprivation worldwide	1.61E-01	4.31E-04	2.55E-03	9.22E-04	0*	9.22E-04	5.46E-03	1.23E-02
Emission of fine particles	1.76E-08	incidence of diseases	1.24E-08	1.03E-09	1.89E-09	5.39E-10	0*	5.39E-10	1.80E-09	1.48E-09

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



Total Life Cycle			Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Ionizing radiation, human health	1.75E+00	kBq of U235 equiv.	1.71E+00	2.61E-04	1.53E-02	1.28E-02	0*	1.28E-02	1.33E-02	1.99E-02
Ecotoxicity (fresh water)	1.46E+01	CTUe	1.22E+01	1.96E-01	1.26E+00	2.25E-02	0*	2.25E-02	9.54E-01	1.12E+00
Human toxicity, carcinogenic effects	3.33E-09	CTUh	3.31E-09	1.51E-12	1.01E-11	1.83E-12	0*	1.83E-12	9.92E-12	3.67E-09
Human toxicity, non-carcinogenic effects	7.43E-09	CTUh	6.43E-09	3.12E-11	4.11E-10	4.98E-11	0*	4.98E-11	5.06E-10	-1.17E-09
Impacts related to land use/soil quality	1.45E-01	-	1.43E-01	2.93E-05	8.90E-04	2.77E-04	0*	2.77E-04	7.94E-04	2.91E-02
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	6.47E-01	MJ	4.77E-01	3.84E-04	6.60E-02	5.18E-02	0*	5.18E-02	5.17E-02	-7.62E-02
Use of renewable primary energy resources used as raw materials	7.51E-01	MJ	7.51E-01	0*	0*	0*	0*	0*	0*	4.99E-01
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	1.40E+00	MJ	1.23E+00	3.84E-04	6.60E-02	5.18E-02	0*	5.18E-02	5.17E-02	4.23E-01
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	1.26E+01	MJ	1.05E+01	2.46E-01	7.69E-01	3.19E-01	0*	3.19E-01	7.66E-01	-1.58E+00
Use of non-renewable primary energy resources used as raw materials	3.18E+00	MJ	3.18E+00	0*	0*	0*	0*	0*	0*	7.04E-01
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	1.58E+01	MJ	1.37E+01	2.46E-01	7.69E-01	3.19E-01	0*	3.19E-01	7.66E-01	-8.73E-01

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



Total Life Cycle			Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Use of secondary materials	5.80E-02	kg	5.80E-02	0*	0*	0*	0*	0*	0*	0*
Use of renewable secondary fuels	0	MJ	0*	0*	0*	0*	0*	0*	0*	0*
Use of non-renewable secondary fuels	0	MJ	0*	0*	0*	0*	0*	0*	0*	0*
Net use of fresh water	4.02E-03	m3	3.78E-03	1.00E-05	5.85E-05	2.15E-05	0*	2.15E-05	1.52E-04	2.86E-04
Hazardous waste disposed of	7.25E-01	kg	5.95E-01	0*	4.17E-02	3.52E-04	0*	3.52E-04	8.76E-02	-2.44E-01
Non-hazardous waste disposed of	1.43E-01	kg	1.11E-01	6.33E-04	5.75E-03	2.39E-03	0*	2.39E-03	2.28E-02	3.77E-02
Radioactive waste disposed of	6.17E-05	kg	5.59E-05	5.01E-07	2.35E-06	4.76E-07	0*	4.76E-07	2.49E-06	1.87E-05
Components for re-use	0	kg	0*	0*	0*	0*	0*	0*	0*	0*
Materials for recycling	2.31E-02	kg	5.40E-03	0*	0*	0*	0*	0*	1.78E-02	0*
Materials for energy recovery	0	kg	0*	0*	0*	0*	0*	0*	0*	0*
Exported energy	0	MJ by energy vector	0*	0*	0*	0*	0*	0*	0*	0*
Total use of primary energy during the life cycle	1.72E+01	MJ	1.49E+01	2.47E-01	8.35E-01	3.71E-01	0*	3.71E-01	8.18E-01	-4.50E-01
Biogenic carbon content of the product	0	kg of C.	0*	0*	0*	0*	0*	0*	0*	0*
Biogenic carbon content of the associated packaging	2.81E-02	kg of C.	2.81E-02	0*	0*	0*	0*	0*	0*	1.19E-02

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

The values of the indicators defined in the PCR-ed4-EN-2021 09 06 are available in the digital database of pep-ecopassport.org website.

Product Environmental Profile

RJ45 Socket ALTAIR range Category 5E



For products covered by the PEP other than the Reference product, the environmental impacts of each phase of the lifecycle are calculated with the coefficients below on those of the Reference Product.

Reference	Designation	Total Life Cycle	Manufacturing	Distribution	Installation	Use	End of life
AC4300MW1 + AC1100MW + A1402	1 Module RJ45 CAT5E UTP Socket Matt White + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.0
AC4300MT1 + AC1100MT1 + A1402	1 Module RJ45 CAT5E UTP Socket Matt Titane + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.0
AC4300MB1 + AC1100MB1 + A1402	1 Module RJ45 CAT5E UTP Socket Matt Black + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.0
AC4307MT1 + AC1102MT1 + A1402	2 Module RJ45 CAT5E UTP Socket Matt Titane + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.1
AC4307MT4 + AC1102MT1 + A1402	2 Module RJ45 CAT5E UTP Socket Matt Titane + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.1
AC4307MB1 + AC1102MB1 + A1402	2 Module RJ45 CAT5E UTP Socket Matt Black + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.1
AC4307MB4 + AC1102MB1 + A1402	2 Module RJ45 CAT5E UTP Socket Matt Black + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.1
AC4307MW1 + AC1102MW1 + A1402	2 Module RJ45 CAT5E UTP Socket Matt White + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.1
AC4307MW4 + AC1102MW1 + A1402	2 Module RJ45 CAT5E UTP Socket Matt White + Plate + Support frame	1.0	1.0	1.0	1.0	1.0	1.1

Registration number: LGRP-02021-V01.01-EN	Drafting rules: « PEP-PCR-ed4-EN-2021 09 06 » Supplemented by «PSR-0005-ed3.1-2023 12 08»
Verifier accreditation N°: VH08	Information and reference documents: www.pep-ecopassport.org
Date of issue: 06-2025	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2006	
Internal ☐ External ☒	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)	
PEP are compliant with NF C08-100-1 :2016 and EN 50693 :2019 or NF E38-500 :2022	
The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2006: «Environmental labels and declarations. Type III environmental declarations»	



Environmental data in alignment with EN 15804: 2012 + A2 : 2019