

Product Environmental Profile

Lighting outlet position

PEP
ECO
PASS
PORT®

■ BTICINO'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

- Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.


- Involve the environment in product design and provide informations in compliance with ISO 14025

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



■ REFERENCE PRODUCT

Function	Establish, support and interrupt a rated current not exceeding 10A and rated voltage 250V for a wallmounted installation, according to the appropriate use scenario, for the reference service life of the product of 20 years.		
			
BT-JA4803JW		BT-J4703M3	
coverplate 3 modules		supporting frame 3 modules	
Reference Product			
	BT-JW4001	BT-JW4003	BT-JW4950
	1way switch 10AX 1m	2way switch 10AX 1m	blank plate

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



■ PRODUCTS CONCERNED

The environmental data is representative of the following products:

BT-JA4803JW	BT-J4703M3	BT-J4803JWQ	BT-JW4001	BT-JW4003	BT-JW4950
BT-JA4803JW/-JG/-TS/-TI/-TD/-JB/-EA/-TR/-ES/-TA/-EN/-TB/-TC/-EM		BT-JA4803JWQ/-JGQ/-TSQ/-TIQ/-TDQ/-JBQ/-TCQ	BT-JW4001 BT-JG4001 BT-JB4001 BT-JW4001Q BT-JB4001Q	BT-JW4003 BT-JG4003 BT-JB4003 BT-JW4003Q BT-JB4003Q	BT-JW4950 BT-JG4950 BT-JB4950 BT-JW4950Q BT-JB4950Q

Product Environmental Profile

Lighting outlet position



CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

Total weight of Reference Product	0.11 kg (all packaging included)
--	---

Product alone weight 0.08 kg					
Plastics as % of weight		Metals as % of weight		Other as % of weight	
ABS	39.2 %	Steel	10.5 %		
PC	12.9 %	Copper and copper alloys	5.5 %		
PP	7.9 %	Silver alloys	0.1%		
PA	0.2 %				
Various plastics	<0.1 %				

Packaging (alone) : 0.03 kg					
PE	0.2 %			Cardboard	16.1 %
				Wood	5.3 %
				Paper	2.1 %

Total plastics : 0.06 kg	60.4 %	Total metals : 0.02 kg	16.1 %	Total others : 0.03 kg	23.5 %
---------------------------------	---------------	-------------------------------	---------------	-------------------------------	---------------

At the date of edition of this document, the content of recycled material(s) is :

- Product alone (excluding packaging): 20 % by mass
- Packaging only: 59 % by mass



MANUFACTURE

This Reference Product comes from site that has received ISO14001 certification. The final assembly site is located in Mexico.



DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 3500 km by road from our warehouse to the local point of distribution into the Latin America market.

Packaging is compliant with applicable regulation.



INSTALLATION

For the installation of the product, only standard tools are needed.



USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

Product Environmental Profile

Lighting outlet position



■ END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.



■ ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life. It is representative of products marketed and used in Latin America.
The datasets collected in this PEP are representative of the year 2025.

For each phase, the following modelling elements were taken in account:

System Limit	Manufacture A1-A3	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
	Distribution A4	Transport between the last Group distribution centre and an average delivery point in the sales area.
	Installation A5	The end of life of the packaging.
	Use B1-B7	<ul style="list-style-type: none">Product category: Switches Wall-mounted. PSR0005 ed3.1 § 3.7. Specific rules for the 'Switches' family.Use scenario: non-continuous operation for 20 years at 10% of rated load, during 30% of the time. This modelling duration does not constitute a minimum durability requirement..Energy model: Electricity Mix_Low voltage_2022_Mexico_MX.
	End of life C1-C4	The default end of life scenario maximizing the impacts.
	D Module	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and burdens beyond the boundaries of the system, and are not to be included in the life cycle totals.
	Software and data-base used	The set of indicators used is Indicators for PEF EF 3.1 (compliant: PEP ed.4, EN15804+A2) v2.0 EIME V6 and its CODDE-2025-04-15 database

Unless otherwise indicated the modelling energetic mix are those integrated in the data modules used from the aformentioned database.

Product Environmental Profile

Lighting outlet position



ENVIRONMENTAL IMPACTS

	Total Life Cycle		Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Climate change - total	5.68E-01	kg CO ₂ eq.	3.15E-01	1.50E-02	4.78E-02	1.43E-01	0.00E+00	1.43E-01	4.74E-02	-2.06E-02
Climate change - fossil fuels	5.61E-01	kg CO ₂ eq.	3.48E-01	1.50E-02	8.71E-03	1.42E-01	0.00E+00	1.42E-01	4.71E-02	2.69E-04
Climate change - biogenics	7.41E-03	kg CO ₂ eq.	-3.23E-02	0*	3.91E-02	3.58E-04	0.00E+00	3.58E-04	3.09E-04	-2.08E-02
Climate change - land use and land use transformation	1.11E-05	kg CO ₂ eq.	1.11E-05	2.18E-08	0*	0.00E+00	0.00E+00	0.00E+00	1.15E-08	8.85E-06
Ozone depletion	6.66E-08	kg CFC-11 eq.	6.33E-08	1.72E-10	3.15E-10	2.51E-10	0.00E+00	2.51E-10	2.61E-09	7.77E-10
Acidification (AP)	2.51E-03	mole of H+ eq.	1.71E-03	2.38E-05	5.11E-05	4.31E-04	0.00E+00	4.31E-04	2.96E-04	-3.14E-05
Freshwater eutrophication	1.92E-06	kg P eq.	1.71E-06	5.52E-08	1.07E-08	4.12E-08	0.00E+00	4.12E-08	1.05E-07	2.45E-07
Marine aquatic eutrophication	3.83E-04	kg of N eq.	2.44E-04	4.56E-06	1.23E-05	6.26E-05	0.00E+00	6.26E-05	5.89E-05	1.13E-05
Terrestrial eutrophication	4.30E-03	mole of N eq.	2.60E-03	5.00E-05	1.64E-04	7.21E-04	0.00E+00	7.21E-04	7.67E-04	5.85E-05
Photochemical ozone formation	1.37E-03	kg NMVOC eq.	9.32E-04	1.60E-05	3.45E-05	2.08E-04	0.00E+00	2.08E-04	1.75E-04	-8.70E-07
Depletion of abiotic resources - elements	1.93E-04	kg Sb eq.	1.93E-04	0*	0*	2.33E-08	0.00E+00	2.33E-08	0*	-4.59E-07
Depletion of abiotic resources - fossil fuels	1.22E+01	MJ	8.62E+00	2.63E-01	1.63E-01	2.32E+00	0.00E+00	2.32E+00	8.59E-01	-9.18E-01
Water requirement	1.75E-01	m ³ deprivation worldwide eq.	1.62E-01	5.35E-04	5.15E-04	6.08E-03	0.00E+00	6.08E-03	5.75E-03	-1.37E-02
Emission of fine particles	1.71E-08	incidence of diseases	1.14E-08	2.09E-10	3.54E-10	3.16E-09	0.00E+00	3.16E-09	1.97E-09	-1.49E-10

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

Product Environmental Profile

Lighting outlet position



	Total Life Cycle		Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Ionizing radiation, human health	8.60E-01	kBq of U235 eq.	8.17E-01	5.01E-04	3.33E-03	2.12E-02	0.00E+00	2.12E-02	1.80E-02	5.00E-03
Ecotoxicity (fresh water)	1.05E+01	CTUe	8.65E+00	4.12E-01	2.19E-01	8.81E-02	0.00E+00	8.81E-02	1.09E+00	2.69E-01
Human toxicity, carcinogenic effects	6.27E-09	CTUh	6.24E-09	2.77E-12	1.62E-12	1.49E-11	0.00E+00	1.49E-11	1.14E-11	2.53E-09
Human toxicity, non-carcinogenic effects	1.09E-08	CTUh	1.01E-08	5.82E-11	6.44E-11	1.78E-10	0.00E+00	1.78E-10	5.39E-10	-6.39E-10
Impacts related to land use/soil quality	4.12E-02	-	3.67E-02	6.16E-05	1.95E-04	3.35E-03	0.00E+00	3.35E-03	8.79E-04	2.39E-02
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	6.66E-01	MJ	2.97E-01	8.09E-04	1.44E-02	2.83E-01	0.00E+00	2.83E-01	7.06E-02	-4.29E-02
Use of renewable primary energy resources used as raw materials	2.77E-01	MJ	2.77E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.68E-01
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	9.43E-01	MJ	5.74E-01	8.09E-04	1.44E-02	2.83E-01	0.00E+00	2.83E-01	7.06E-02	2.26E-01
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	9.75E+00	MJ	6.15E+00	2.63E-01	1.63E-01	2.32E+00	0.00E+00	2.32E+00	8.59E-01	-7.12E-01
Use of non-renewable primary energy resources used as raw materials	2.48E+00	MJ	2.48E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-2.06E-01
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	1.22E+01	MJ	8.62E+00	2.63E-01	1.63E-01	2.32E+00	0.00E+00	2.32E+00	8.59E-01	-9.18E-01

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

Product Environmental Profile

Lighting outlet position



	Total Life Cycle		Manufacturing	Distribution	Installation	Use ⁽¹⁾			End of Life	Module D
			A1-A3	A4	A5	Total B1-B7	B2	B6	C1-C4	
Use of secondary materials	3.48E-02	kg	3.48E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	4.11E-03	m ³	3.79E-03	1.25E-05	1.18E-05	1.42E-04	0.00E+00	1.42E-04	1.52E-04	-3.19E-04
Hazardous waste disposed of	8.23E-01	kg	7.05E-01	0*	9.49E-03	8.97E-04	0.00E+00	8.97E-04	1.07E-01	-3.50E-02
Non-hazardous waste disposed of	1.50E-01	kg	1.13E-01	1.34E-03	1.18E-03	1.70E-02	0.00E+00	1.70E-02	1.80E-02	1.78E-02
Radioactive waste disposed of	7.42E-05	kg	6.29E-05	1.06E-06	4.93E-07	7.02E-06	0.00E+00	7.02E-06	2.75E-06	7.37E-06
Components for re-use	0.00E+00	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	2.79E-02	kg	5.24E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.27E-02	0.00E+00
Materials for energy recovery	0.00E+00	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	0.00E+00	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of primary energy during the life cycle	1.32E+01	MJ	9.20E+00	2.63E-01	1.77E-01	2.61E+00	0.00E+00	2.61E+00	9.30E-01	-6.92E-01
Biogenic carbon content of the product	0.00E+00	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the associated packaging	1.26E-02	kg of C	1.26E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	6.37E-03

*Represents less than 0.01% of the total life cycle of the reference flow

⁽¹⁾ For the Use phase and according to the current PCR, the information modules B1, B3, B4, B5 and B7, all having indicator values equal to «0» (zero), are not listed in this table

In accordance with current PCR rules, the environmental indicator values in the «Module D» column must not be summed with the values in the «Total Life Cycle» column

The values of the indicators defined in the PCR-ed4-EN-2021 09 06 are available in the digital database of pep-ecopassport.org website.

The environmental impacts are calculated for a configuration composed by one 1 way switch, one 2 way switch, one blank plate, one support 3 modules and one coverplate 3 modules. For products covered by the PEP other than the Reference Product, the environmental impacts of each phase of the lifecycle are assimilated to the impacts of the Reference Product.

Product Environmental Profile

Lighting outlet position



Registration number: LGRP-02170-V01.01-EN	Drafting rules: « PEP-PCR-ed4-EN-2021 09 06 » Supplemented by «PSR-0005-ed3.1-2023 12 08»
Verifier accreditation N°: VH08	Information and reference documents: www.pep-ecopassport.org
Date of issue: 09-2025	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2006	
<input checked="" type="checkbox"/> Internal	<input checked="" type="checkbox"/> External
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDomain)	
PEP are compliant with NF C08-100-1:2016 and EN 50693 :2019 or NF E38-500 :2022	
The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2006: «Environmental labels and declarations. Type III environmental declarations»	

Environmental data in alignment with EN 15804: 2012 + A2 : 2019