

128, Av. du Maréchal-de-Lattre-de-Tassigny 87045 Limoges cedex - France Tel: +33 (0)5 55 06 87 87 Fax: +33 (0)5 55 06 88 88



Your usual Sales office Website: <u>www.legrand.fr</u>

Product Environmental Profile XL3 Isolating distribution cabinet 3 rows

PEP conforme au Programme "PEP ecopassport" selon les règles PEP-AP001 (Informations sur le site internet du programme : www.pep-ecopassport.org). Les règles d'analyse du cycle de vie sont disponibles sur demandes auprès de l'entreprise.



Legrand's environmental commitments

> Incorporate environmental management into our industrial units.

At present, 81 % of units worldwide and 92 % of our European units are ISO 14001-certified.



> Involve the environment in product design.

Provide our customers with all relevant information (composition, consumption, end of life, etc.). Reduce the environmental impact of products over their whole life cycle.

> Offer our customers environmentally friendly solutions.

Develop innovative solutions to help our customers design installations that consume less energy, are better managed and more environmentally friendly.



Product description

> Reference products for this environmental profile

The given values are based on the following items.

Function	XL3 160 Isolating distribution cabinet – all modules – 3 rows – 900x575x147 – DPX space XL3 160 Isolating distribution cabinet – all modules – 4 rows – 1050x575x147 – DPX space		
Reference products	Cat. No. 200 95 XL3 160 Isolating distribution cabinet – fully modular – 3 rows – 900x575x147 – DPX space		

> Products covered by this product environmental profile

Environmental impacts of the reference products are representative of the products covered by this PEP, which therefore constitute a homogeneous environmental family.

Cat. Nos 200 95/96

Llegrand[®]

Product Environmental Profile XL3 Isolating distribution cabinet 3 rows

Constituent materials

These products contain no substances forbidden by regulations applicable at the time of their market launch, excluding maintenance operations carried out during normal use.

Total weight of reference products: 12.9 kg (unit packaging included)

Plastics as % of weight	Metals as % of weig	Other as % of weight			
PVC	50.52 %	Steel	18.47 %		
PS	11.56 %	Copper	1.44 %		
ABS	3.46 %	Aluminium	1.25 %		
PA6/PA66	1.64 %	Lead	50 ppm		
PE	0.03 %				
PP	0.02 %				
				Packaging as % of weight	
				Paper/cardboard	11.61 %
Total plastics	67.22 %	Total metals	21.17 %	Total others	11.61 %

19.48 % by weight

Estimated recycled material content:

Calculated on the basis of data on recycling in France, source: "Bilan du recyclage 1993-2003, Données et références", 2005 edition, published by the French Agency for the Environment and Energy Control (ADEME)

1/1/ Manufacture

These products are manufactured by a Legrand Group production unit which has received ISO 14001 environmental certification for manufacturing.

Įβ **Distribution**

Typical transport conditions

On average this product covers 1,000 km by road transport from our production site to the nearest distributor to our customer. (Basis for calculation: average distance calculated for products sold in France)

Packaging

- The 1,496 g packaging is composed of: 100 % paper/cardboard
- Recycling potential: 100 % by weight of packaging •
- Energy recovery potential: 100 % by weight of packaging
- The packaging has been designed in accordance with the current applicable regulations:
 - Directive 94/62/EC concerning packaging and packaging waste
 - Decree 98-638 transposing the Directive into French law. •

Legrand undertakes to:

- Reduce its packaging at source as much as possible in terms of weight and volume, in accordance with its customers' needs.
- Produce packaging with a heavy metal content of <100 ppm and without deliberately introducing N-class environmentally hazardous substances.
- Design and use packaging that is convertible and where possible reusable.



Product Environmental Profile XL3 Isolating distribution cabinet 3 rows



Use scenario

Electrical products can be divided into two main product families: "passive" or "active" products. Passive products dissipate energy through the joule effect, whereas active products consume power (motor, lighting, etc.). In all cases a use scenario must be defined to quantify the energy consumed.

This product consumes no power during use.

Consumable

No consumables are necessary to use the product.

Servicing and maintenance

Normal conditions of use of this type of product require no servicing or maintenance.



Product management

- > Hazardous waste contained in the product: This product contains no hazardous waste.
- > Non-hazardous waste contained in the product:

Plastics / metal / others: 1.29 kg

> Recycling potential:

The recycling potential of a product is the percentage of material that can be recycled using existing techniques. It takes no account of the existence or lack of recycling chains, which are highly dependent on the local situation.

This product contains 100 % by weight of recyclable material (excluding packaging):

- Plastic materials : 76 %
- Metal materials : 24 %
- > Energy recovery potential:

Energy recovery consists in valorising the calories contained in waste by burning it and recovering the energy produced, for example, to heat buildings or to produce electricity. The process uses the convertible energy embodied in the waste.

This product contains 76 % by weight of materials that can be recovered for energy production (excluding packaging).

Product Environmental Profile XL3 Isolating distribution cabinet 3 rows



Environmental impacts

Methodology

The environmental impacts of the reference product are representative of the products covered by the PEP, which therefore constitute a homogeneous environmental family.

Assessment of the environmental impacts of the reference product concerns the following stages of the life cycle: raw materials, manufacture, distribution, and use.

The modelling assumptions for use are:

• No energy consumption, no consumables, no product maintenance.

Indicators (see glossary)	Unit	Overall M+D+U	Manufacture M	Distribution D	Use U
Depletion of natural resources	years -1	1.71E-14	99.66 %	0.34 %	0 %
Total energy consumed	MJ	1120	96.08 %	3.92 %	0 %
Consumption of water	dm ³	517	99.22 %	0.78 %	0 %
Contribution to the greenhouse effect	g~CO ₂	6.21E+04	91.90 %	8.10 %	0 %
Contribution to the depletion of the ozone layer	g~CFC ₁₁	1.13E-02	69.74 %	30.26 %	0 %
Contribution to the creation of photochemical ozone	g~C ₂ H ₄	8.29E+01	87.40 %	12.60 %	0 %
Potential for acidification of the air	g~H+	41.1	97.90 %	2.10 %	0 %
Production of hazardous waste	kg	0.496	99.74 %	0.26 %	0 %

Modelling performed using EIME software version 1.6 and its database in version 4.3

Extrapolation rule for products other than reference product: the environmental impacts are generally proportional to product weight (i.e. +15% for reference 20096).



	Glossary			
Consumption of water		Indicates the total water consumption for the whole life cycle of the product.		
Contribution to the creation of photochemical ozone		Indicates as $g \sim C_2 H_4$ the gas emissions having an effect on the creation of photochemical ozone in the lower atmosphere (smog) under the effect of solar radiation.		
Contribution to the depletion of the ozone layer		Indicates what all the life cycle phases of the product release as \mbox{CO}_2 gram-equivalents.		
Contribution to the greenhouse effect		Indicates what all the life cycle phases of the product release as CO_2 gravely equivalents. Example of the equivalence principle: 1 g of $CO_2 = 1$ g \sim CO ₂ ; 1 g CH ₄ (methane) is equivalent to the effect of 64 g of CO ₂ , etc.		
Convertible		Said of a product or packaging capable of being reused, recycled or from which it is possible to recover energy by incineration.		
Depletion of natural resources		Indicates the depletion of natural resources, by considering the quantity of wo reserves (minerals, fossils, etc.) for these resources and the current level consumption. Expressed as a fraction of the reserves that disappear each year.		
Eco-solution		Products or services enabling the reduction of a building's environmental impacts.		
EIME		Environmental Information and Management Explorer - Product environmental impact modelling software based on the life cycle assessment methodology.		
Energy recovery potential		% by weight of the product or packaging from which energy can be recovered. Energy recovery consists in valorising the calories contained in waste by burning i and recovering the energy produced, for example, to heat buildings or to produce electricity. The process uses the convertible energy embodied in the waste.		
Hazardous v	vaste	This is specific waste having a certain level of toxicity and requiring special treatment. Its definition is codified by the European community (Annex of Decision 2000/532/EC amended by Decisions 2001/118/EC and 2001/119/EC)		
LCA		Compilation and assessment of inputs and outputs, as well as the potential environmental impacts of a product, or a system, during its life cycle, "from the cradle to the grave". This approach is described by standard ISO 14040 and its related standards.		
Life cycle ap	pproach	Method of taking into account all the life stages of a product (manufacture, installation, use and end of life) in order to determine the consequences for the environment.		
Non-hazardo	ous waste	This is made up of non-toxic waste and is of a similar nature to household waste. Its definition is codified by the European community (Annex of Decision 2000/532/EC amended by Decisions 2001/118/EC and 2001/119/EC)		
Potential for	acidification of the air	Indicates the potential for acidification of the air caused by the release of certain gases into the atmosphere. Expressed as H^{\star} ion gram-equivalent.		
Production of	of hazardous waste	Indicates the weight of ultimate hazardous waste produced for the whole life cycle of the product.		
Recycling po	otential	% by weight of the product or packaging capable of being re-injected into a manufacturing circuit of the same product or another product.		
Reference product(s)		Product (or product group) modelled in the presented LCA.		
Reusable		Said of a product or packaging capable of being used for the same function provided the product's proper functionality is verified by the person carrying out the operation.		
Total energy	/ consumed	Indicates the total energy consumption in megajoules for the whole life cycle of the product.		
WEEE (Waste Electrical and Electronic Equipment)		For products in the application area of the European Directive on Waste Electronic and Electrical Equipment (2002/96/EC), part of the product having to be treated selectively in compliance with Annex II of the Directive.		