

SAFETY DATA SHEET

Legrand has assembled this battery without modifying it and in accordance with the battery manufacturer's instructions for the following finished products:

| |
|-----------|
| LG-661460 |
| LG-660460 |
| LG-062631 |
| UR-130037 |
| UR-130036 |
| LG-660976 |
| UR-111923 |

Material Safety Data Sheet For LiFePO4 Batteries

Issue Date: January 1, 2025

Section 1- Product Identification

Product Name: Lithium Iron Phosphate Battery
 Nominal Voltage: HB00127TA 6,4V 3,2Ah 20,48Wh
 Chemical System: LiFePO₄/C
 Manufacturer Name: JYH Technology Co., Ltd.
 Phone Number: +86-750-3808313
 Fax Number: +86-750-3808133

Section 2- Composition /Information on Ingredients

Although the chemical composition of the various cell manufacturers is proprietary, the following is typical of the chemistry.

| Chemical Name | CAS No. | % |
|---|------------|-------|
| Aluminum Foil | 7429-90-5 | 5-10 |
| Copper Foil | 7440-50-8 | 10-15 |
| dimethyl carbonate (DMC) | 616-38-6 | 5-20 |
| Diethyl carbonate (DEC) | 105-58-8 | 5-20 |
| Ethylene Carbonate (EC) | 96-49-1 | 5-20 |
| Graphite Powder | 7440-44-0 | 15-20 |
| Lithium Iron Phosphate (LiFePO ₄) | 14365-14-7 | 35-45 |
| Lithium Hexafluorophosphate | 21324-40-3 | 1-5 |
| Poly Vinylidene Fluoride (PVDF) | 24937-79-9 | 0.1-1 |
| Iron | 7439-89-6 | 5-15 |
| Nickel | 7440-02-0 | 0.1-2 |

Section 3- Hazard Identification

3.1 Physical:

The Lithium Iron Phosphate batteries described in this Material Safety Data Sheet are sealed which are not hazardous when used according to the recommendations of the manufacturer.

Under normal conditions of use, electrode materials and liquid electrolyte they contain are non-reactive provided the battery integrity is maintained and seals remain intact, Risk of exposure only in case of abuse, e.g. mechanical, thermal, electrical, which leads to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water of battery vent/ explosion/fire may follow depending upon circumstances.

3.2 Chemical:

Classification of dangerous Substances Contained into the Product as per Directive

| Substance | Chemical Symbol | Melting Point | Boiling point | Exposure limit | Indication of Danger | Special Risk* | Safety Advice** |
|------------------------|---------------------|---------------|---------------|--------------------------|----------------------|-------------------------|----------------------------------|
| Lithium Iron Phosphate | LiFePO ₄ | >1000°C | | 0.1 mg/m3 OSHA | | R22R43 | S2 S22 S24 S26 S36 S37 S45 |
| Organic Solvents | EC | EC: 38°C | EC: 243°C | None established OSHA | Flammable | R21R22 R41 R42/43 | S2 S24 S26 S36 S37 S45 |
| | DMC | DMC: 4°C | DMC: 90°C | | | | |
| | DEC | DEC: -43° | DEC: 127°C | | | | |
| | LiPF ₆ | N/A | N/A | None | Irritant | R14R21 | S2 S8 S22 |

Material Safety Data Sheet For LiFePO4 Batteries

| | | | | | | | |
|--|--|-----------------------|--|------------------|-----------|-------------------|------------------------|
| | | (decomposes at 160°C) | | established OSHA | Corrosive | R22 R41 R43 | S24 S26 S36 S37 S45 |
|--|--|-----------------------|--|------------------|-----------|-------------------|------------------------|

***: Name of Special Risks:**

- R14/15 Reacts with water and yields flammable gases
- R21 Harmful in contact with skin
- R22 Harmful us swallowed
- R35 Causes severe burns
- R41 Risk of serious damage to the eye
- R42/43 May cause sensitization by inhalation and skin contact
- R43 May cause sensitization by skin contact

****: Name of Safety Advices:**

- S2 Keep out of reach from children
- S8 Keep away from moisture
- S22 Do not breathe dust
- S24 Avoid contact with skin
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical attention
- S36 Wear suitable protective clothing
- S37 Wear suitable gloves
- S45 In case of incident, seek medical attention

Section 4- First Aid Measures

In case of battery rupture or explosion, evacuate personnel from contaminated area and provide maximum ventilation to clear out corrosive fumes/gases and pungent odors.

In all case, seek immediate medical attention,

Eye contact: Flush with plenty of water(eyelids-held open)for at least 15 minutes

Skin contact: Remove all contaminated clothing and flush affected areas with plenty of water and sop for at least 15minutes.

Ingestion: Dilute by giving plenty of water and get immediate medical attention.

Assure that the victim does not aspirate vomited material by use of positional drainage.

Assure that mucus does not obstruct the airway.

Do not give anything by mouth to an unconscious person

Inhalation: Remove to fresh air and ventilate the contaminated area.

Give oxygen or artificial respiration if needed.

Section 5- Fire and explosion Hazard Data

| | |
|---------------------------|---|
| Fire and explosion hazard | The batteries can leak and/or spout vaporized or decomposed and combustible electrolyte fumes in case of exposure above 90°C resulting from inappropriate use or from the environment. Possible formation of hydrogen fluoride (HF) and phosphorous oxides during fire.LiPF6 salt contained in the electrolyte releases hydrogen fluoride (HF) in contact with water. |
| Extinguishing media | Suitable: CO ₂ , |

Material Safety Data Sheet For LiFePO4 Batteries

| | |
|------------------------------|--|
| | Dry chemical or Foam extinguishers Not to be used: Type D extinguishers |
| Special exposure hazards: | Following cell overheating due to external source or due to improper use, electrolyte leakage or battery container rupture may occur and release inner component/material in the environment. Eye contact: The electrolyte solution contained in the battery is irritant to ocular tissues. Skin contact: The electrolyte solution contained in the battery causes skin irritation. Ingestion: The ingestion of electrolyte solution causes tissue damage to throat and gastro/respiratory tract. Inhalation: Contents of a leaking or ruptured battery can cause respiratory tract, mucus, membrane irritation and edema. |
| Special protective equipment | Use self-contained breathing apparatus to avoid breathing irritant fumes. Wear protective clothing and equipment to prevent body contact with electrolyte solution. |

Section 6- Accidental Release or Spillage

| | |
|--|---|
| Personal Precautions, protective equipment, and emergency procedures | Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8. |
| Environmental Precautions | Prevent material from contaminating soil and from entering sewers or waterways. |
| Methods and materials for Containment | Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately. |
| Methods and materials for cleaning up | Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal. |

Section 7- Handling and Storage

The batteries should not be opened destroyed nor incinerated since they may leak or rupture and release in the environment the ingredients they contain.

| | |
|-----------------|--|
| Handling | Do not crush, pierce, short (+) and (-) battery terminals with conductive (i.e. metal) goods. Do not directly heat or solder. Do not throw into fire. Do not mix batteries of different types and models. Do not mix new and used batteries. Keep batteries in non-conductive (i.e. plastic) trays. |
| Storage | Store in a cool (preferably below 30°C) and ventilated area away from moisture, sources of heat, open flames, food and drink. Keep adequate clearance between walls and batteries. Temperature above 90°C may result in battery leakage and rupture. Since short circuit can |

Material Safety Data Sheet For LiFePO4 Batteries

| | |
|--------------|---|
| | cause burn, leakage and rupture hazard, keep batteries in original packaging until use and do not jumble them. |
| Other | Manufacturer recommendations regarding maximum recommended currents and operating temperature range. Applying pressure on deforming the battery may lead to disassembly followed by eye, skin and throat irritation. |

Section 8- Exposure Controls / Person Protection

| | |
|------------------------|---|
| Respiratory protection | Not necessary under normal use. In case of battery rupture, use self-contained full-face respiratory equipment. equipment with type ABEK filter. |
| Hand protection | Not necessary under normal use. Use rubber gloves if handling a leaking or ruptured battery. |
| Eye protection | Not necessary under normal use. Wear safety goggles or glasses with side shields if handling a leaking or ruptured battery. |
| Skin protection | Not necessary under normal use. Use rubber apron and protective working in case of handling of a ruptured battery. |

Section 9- Physical and Chemical Data

9.1 Appearance (Physical shape and color as supplied:)

| | |
|---------------------|---------------------------------------|
| LiFePO ₄ | Black odorless power |
| Graphite | Black odorless power |
| Organic solvent | Colorless liquid |
| Lithium salt | White, crystalline and odorless power |

9.2 Specific gravity (H₂O=1)

| | |
|---------------------|---------|
| LiFePO ₄ | 3.63 |
| Graphite | 2.0-2.2 |

9.3 Melting point

| | |
|---------------------|-------------|
| LiFePO ₄ | > 1000°C |
| Graphite | 3500-3900°C |

Section 10-Stability and Reactivity Data

| | |
|----------------------------------|---|
| Stability | Stable under normal temperatures and pressures. |
| Conditions to avoid | Heat above 70°C or incinerate. Deform, mutilate, crush, pierce, disassemble. Short circuit. Prolonged exposure to humid conditions. |
| Materials to avoid | N/A |
| Hazardous decomposition products | Corrosive/Irritant Hydrogen fluoride (HF) is produced in case of reaction of lithium (LiPF ₆) with water. Combustible vapors and formation of Hydrogen fluoride (HF) and phosphorous oxides during fire. Toxic fumes, and may form peroxides. |

Section 11- Toxicological information

| | |
|------------|---|
| Irritation | In the event of exposure to internal contents, vapor/fumes may be very irritating |
|------------|---|

Material Safety Data Sheet For LiFePO4 Batteries

| | |
|--------------------------------------|-----------------------|
| | to the eyes and skin. |
| Sensitization | No data is available |
| Reproductive toxicity | No data is available |
| Toxicologically synergistic material | No data is available |

Section 12- Ecological Information

| | |
|-------------------------------|--|
| General note | Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. |
| Mobility in soil | No data is available |
| Persistence and degradability | No data is available |

Section 13- Disposal Method

Dispose in accordance with applicable regulations which vary from country to country.

(In more countries, the thrashing of used batteries is forbidden and the end-users are invited to dispose them properly, eventually through not-for-profit organizations, mandated by local governments or organized on a voluntary basis by professionals).

Lithium Iron Phosphate batteries should have their terminals insulated and be preferably wrapped in plastic bags prior to disposal.

13.1 Incineration: Incineration should never be performed by battery users but eventually by trained professionals in authorized facilities with proper gas and fumes treatment.

13.2 Land filling: Leach ability regulations (mg/l)

| Component | Leach ability | EC limit | EPA | Other* |
|-----------|---------------|----------|-----|--------|
| Iron | 100 | 2 | | 5 |
| Nickel | 500 | | | 0.5 |

13.3 Recycling: Send to authorized recycling facilities, eventually through licensed waste carrier.

Section 14- Transportation Information

14.1 UN number of Lithium Ion batteries: UN3480 or UN3481.

14.2 Lithium Ion batteries have been tested under provisions of the UN Manual of Tests and Criteria, the batteries are passed the UN 38.3 test, Part III, sub-section 38.3 (withstanding a 1.2m drop test) and are classified as Class 9: Miscellaneous dangerous substances and articles.

14.3 The package of battery by air should be complied with the requirements of Packing Instruction 965 (Section II/ Section IB) or 966/967 (Section II) of IATA DGR 66th Edition for transportation. The battery containing Watt-hour rating by air is not more than 100Wh.

14.4 The battery is not restricted according to IMO IMDG Code (inc Amdt 41-22). Need to meet the Special Provision International Maritime dangerous goods code (IMDG) 188.

14.5 The packaging is required to be strong and can prevent the products from short-circuit.

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions.

Material Safety Data Sheet For LiFePO4 Batteries

- The International Air Transport Association (IATA) Dangerous Goods Regulations.
- The International Maritime Dangerous Goods (IMDG) Code.
- The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA
- The Office of Hazardous Materials Safety within the US Department of Transportations' (DOT) Research and Special Programs Administration (RSPA).

Section 15- Regulatory Information

The transport of rechargeable Lithium Iron Phosphate batteries is regulated by various bodies (IATA, IMO, ADR, US-DOT) that follow the United Nations "Recommendations on the Transport of Dangerous Goods, Model Regulations, 23th Revised edition - Ref.ST/SG/AC.10/1 Rev. 23".

Depending on their lithium metal equivalent weight content, design, and ability to pass safety tests defined by the UN in the "Recommendations on the Transport of Dangerous Good - Manual of Tests and Criteria – 7th Revised edition - Ref. ST/SG/AC.10/11 Rev.7 Amendment 1 «Lithium Batteries»", the Lithium Iron Phosphate cells and the battery packs are not be assigned to the UN N°3480/3481 Class-9, that is restricted for transport.

Section 16- Other Information

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

JYH does not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information. JYH does not offer warranty against patent infringement.

Additional information is available by calling the telephone number above designated purpose.