



Pack	Cat. Nos.		<b>RX<sup>3</sup> residential MCBs - 6000 A</b>	
	<b>NEW</b>		Breaking capacity : 6000 A to BS EN 60898-1	
			<b>Single pole - 230/400 V~</b>	
	B curve	C curve	Nominal rating (In)	Number of 17.5 mm modules
12	4197 49	4198 37	6 A	1
12	4197 50	4198 38	10 A	1
12	4197 52	4198 40	16 A	1
12	4197 53	4198 41	20 A	1
12	4197 54	4198 42	25 A	1
12	4197 55	4198 43	32 A	1
12	4197 56	4198 44	40 A	1
12	4197 57	4198 45	50 A	1
12	4197 58	4198 46	63 A	1

B		C		Cat. Nos.		<b>DX<sup>3</sup> MCBs - 6000 A</b>	
						Breaking capacity : 6000 A to BS EN 60898-1	
						<b>Single pole - 230/400 V~</b>	
B	C	B curve	C curve	Nominal rating (In)	Number of 17.5 mm modules		
1	1	4074 29	4076 66	6 A	1		
10	10	4074 30	4076 68	10 A	1		
10	10	4074 32	4076 70	16 A	1		
1	10	4074 33	4076 71	20 A	1		
1	10	4074 35	4076 73	32 A	1		
1	1	4074 36	4076 74	40 A	1		
1	1	4074 37	4076 75	50 A	1		
1	1	4074 38	4076 76	63 A	1		

B curve		Cat. Nos.		<b>RCBOs (combined MCB/RCD) - Single module</b>	
				Breaking capacity : 10 kA to BS EN 61009-1	
				RCD type AC conform to BS EN 61009-1	
				Terminal capacity : rigid conductor 35 mm <sup>2</sup>	
				flexible conductor 25 mm <sup>2</sup>	
				<b>Single pole and neutral - 240 V~</b>	
		Nominal rating (In)	Number of 17.5 mm modules		
1		6 A	1		
1		10 A	1		
1		16 A	1		
1		20 A	1		
1		32 A	1		
1		40 A	1		
1		50 A	1		

Pack	Cat. Nos.		<b>RX<sup>3</sup> residual current devices (RCDs)</b>	
			Conform to BS EN 61008-1	
			Terminal capacity : rigid conductor 35 mm <sup>2</sup>	
			flexible conductor 25 mm <sup>2</sup>	
			<b>Double pole 230 V~</b>	
	Type AC	Nominal rating (In)	Number of 17.5 mm modules	
		<b>30 mA</b>		
1	4020 24	25 A	2	
1	4020 25	40 A	2	
1	4020 26	63 A	2	
1	4020 27	80 A	2	
		<b>100 mA</b>		
1	4020 28	25 A	2	
1	4020 29	40 A	2	
1	4020 30	63 A	2	

5		5		Cat. Nos.		<b>DX<sup>3</sup> isolating switches</b>	
						Conform to BS EN 60947-3, BS EN 60669-1	
						Usage : AC 22 according to BS EN 60947-3	
						Red handle	
						Double break contacts, padlockable	
						50 mm <sup>2</sup> capacity shielded terminals	
						Number of 17.5 mm modules	
5	4064 53	63 A double pole	2				
5	4064 55	100 A double pole	2				

1		Cat. Nos.		<b>CX<sup>3</sup> contactor with 230 V~ coil</b>	
				Conforms to BS EN 61095	
				<b>Double pole (L + N) 250 V~</b>	
				230 V~ coil circuit	
		I max.	Type of contact	Number of 17.5 mm modules	
1	4125 44	25 A	2 N/O	1	

1		1		1		1		1		<b>Bell transformers</b>	
										Conform to BS EN 61558-2-8	
										Supplied with label holder	
										Protected against overloads and short circuits	
										Power to 8 V-12 V or 24 V access control devices such as bells and chimes	
										Possibility for supply busbars to run through (Cat. Nos. 4130 90/91)	
		Secondary (V)	Rating (A)	Power (VA)	Number of 17.5 mm modules						
1	4130 90	<b>230 V / 8 V</b> 8 V~	0.5 A	4 VA	2						
1	4130 91	<b>230 V / 12 V - 8 V</b> 12/8 V~	0.66/1 A	8 VA	2						
1	4130 93	<b>230 V / 24 V - 12 V</b> 24/12 V~	1/1.5 A	24/18 VA	4						