

DMX³ 2500/4000/6300

technical characteristics (continued)

Technical characteristics

DMX³ 2500

DMX ³ according to IEC 60947-2	DMX ³ 2500																		
	800			1000			1250			1600			2000			2500			
	N	H	L	N	H	L	N	H	L	N	H	L	N	H	L	N	H	L	
Number of poles	3P - 4P			3P - 4P			3P - 4P			3P - 4P			3P - 4P			3P - 4P			
Rating In (A)	800			1000			1250			1600			2000			2500			
Rated insulation voltage Ui (V)	1000			1000			1000			1000			1000			1000			
Rated impulse withstand voltage Uimp (kV)	12			12			12			12			12			12			
Rated operational voltage (50/60Hz) Ue (V)	690			690			690			690			690			690			
Frame	2500		4000	2500		4000	2500		4000	2500		4000	2500		4000	2500		4000	
Ultimate breaking capacity Icu (kA)	230 V~	50	65	100	50	65	100	50	65	100	50	65	100	50	65	100	50	65	100
	415 V~	50	65	100	50	65	100	50	65	100	50	65	100	50	65	100	50	65	100
	500 V~	50	65	100	50	65	100	50	65	100	50	65	100	50	65	100	50	65	100
	600 V~	50	60	75	50	60	75	50	60	75	50	60	75	50	60	75	50	60	75
	690 V~	50	55	65	50	55	65	50	55	65	50	55	65	50	55	65	50	55	65
Service breaking capacity Ics (% Icu)	230 V~	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	415 V~	105	143	220	105	143	220	105	143	220	105	143	220	105	143	220	105	143	220
	500 V~	105	143	220	105	143	220	105	143	220	105	143	220	105	143	220	105	143	220
	600 V~	105	132	165	105	132	165	105	132	165	105	132	165	105	132	165	105	132	165
	690 V~	105	121	143	105	121	143	105	121	143	105	121	143	105	121	143	105	121	143
Short-circuit making capacity Icm (kA)	230 V~	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85
	415 V~	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85
	500 V~	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85
	600 V~	50	60	75	50	60	75	50	60	75	50	60	75	50	60	75	50	60	75
	690 V~	50	55	65	50	55	65	50	55	65	50	55	65	50	55	65	50	55	65
Short time withstand current Icw (kA) for t = 1s	230 V~	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85
	415 V~	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85
	500 V~	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85	50	65	85
	600 V~	50	60	75	50	60	75	50	60	75	50	60	75	50	60	75	50	60	75
	690 V~	50	55	65	50	55	65	50	55	65	50	55	65	50	55	65	50	55	65
Category of use	B			B			B			B			B			B			
Isolation behavior	Yes			Yes			Yes			Yes			Yes			Yes			
Endurance (cycles) without maintenance	mechanical	10000			10000			10000			10000			10000			10000		
	electrical	5000			5000			5000			5000			5000			5000		

DMX³ 4000

DMX ³ according to IEC 60947-2	DMX ³ 4000						
	3200			4000			
	N	H	L	N	H	L	
Number of poles	3P - 4P			3P - 4P			
Rating In (A)	3200			4000			
Rated insulation voltage Ui (V)	1000			1000			
Rated impulse withstand voltage Uimp (kV)	12			12			
Rated operational voltage (50/60Hz) Ue (V)	690			690			
Frame	4000			4000			
Ultimate breaking capacity Icu (kA)	230 V~	50	65	100	50	65	100
	415 V~	50	65	100	50	65	100
	500 V~	50	65	100	50	65	100
	600 V~	50	60	75	50	60	75
	690 V~	50	55	65	50	55	65
Service breaking capacity Ics (% Icu)	230 V~	100	100	100	100	100	100
	415 V~	105	143	220	105	143	220
	500 V~	105	143	220	105	143	220
	600 V~	105	132	165	105	132	165
	690 V~	105	121	143	105	121	143
Short-circuit making capacity Icm (kA)	230 V~	50	65	85	50	65	85
	415 V~	50	65	85	50	65	85
	500 V~	50	65	85	50	65	85
	600 V~	50	60	75	50	60	75
	690 V~	50	55	65	50	55	65
Short time withstand current Icw (kA) for t = 1s	230 V~	50	65	85	50	65	85
	415 V~	50	65	85	50	65	85
	500 V~	50	65	85	50	65	85
	600 V~	50	60	75	50	60	75
	690 V~	50	55	65	50	55	65
Category of use	B			B			
Isolation behavior	Yes			Yes			
Endurance (cycles) without maintenance	mechanical	10000			10000		
	electrical	5000			5000		

DMX³ 6300

DMX ³ according to IEC 60947-2	DMX ³ 6300		
	5000	6300	
	L	L	
Number of poles	3P - 4P	3P - 4P	
Rating In (A)	5000	5000	
Rated insulation voltage Ui (V)	1000	1000	
Rated impulse withstand voltage Uimp (kV)	12	12	
Rated operational voltage (50/60Hz) Ue (V)	690	690	
Frame	6300	6300	
Ultimate breaking capacity Icu (kA)	230 V~	100	100
	415 V~	100	100
	500 V~	100	100
	600 V~	75	75
	690 V~	65	65
Service breaking capacity Ics (% Icu)	230 V~	100	100
	415 V~	220	220
	500 V~	220	220
	600 V~	165	165
	690 V~	143	143
Short-circuit making capacity Icm (kA)	230 V~	100	100
	415 V~	100	100
	500 V~	100	100
	600 V~	75	75
	690 V~	65	65
Short time withstand current Icw (kA) for t = 1s	230 V~	100	100
	415 V~	100	100
	500 V~	100	100
	600 V~	75	75
	690 V~	65	65
Category of use	B	B	
Isolation behavior	Yes	Yes	
Endurance (cycles)	mechanical	5000	5000
	electrical	2500	2500

Temperature derating

Fixed version

Temperature	40°C		50°C		60°C		65°C		70°C	
	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n
DMX ³ 2500	800	1	800	1	800	1	800	1	800	1
	1000	1	1000	1	1000	1	1000	1	1000	1
	1250	1	1250	1	1250	1	1250	1	1250	1
	1600	1	1600	1	1600	1	1600	1	1600	1
	2000	1	2000	1	1960	0.98	1920	0.96	1880	0.94
DMX ³ 4000	2500	1	2500	1	2350	0.94	2250	0.9	2150	0.86
	3200	1	3200	1	3200	1	3136	0.98	3008	0.94
DMX ³ 6300	4000	1	4000	1	3680	0.92	3440	0.86	3120	0.78
	5000	1	5000	1	5000	1	5000	1	5000	1
	6300	1	6300	1	6048	0.96	5796	0.92	5544	0.88

Draw-out version

Temperature	40°C		50°C		60°C		65°C		70°C	
	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n	I _{max} (A)	I _r / I _n
DMX ³ 2500	800	1	800	1	800	1	800	1	800	1
	1000	1	1000	1	1000	1	1000	1	1000	1
	1250	1	1250	1	1250	1	1250	1	1250	1
	1600	1	1600	1	1600	1	1600	1	1600	1
	2000	1	2000	1	1960	0.98	1920	0.96	1875	0.94
DMX ³ 4000	2500	1	2500	1	2250	0.9	2100	0.84	1950	0.78
	3200	1	3200	1	3200	1	3072	0.96	2880	0.9
DMX ³ 6300	4000	1	4000	1	3440	0.86	3200	0.8	2960	0.74
	5000	1	5000	1	5000	1	5000	1	5000	1
	6300	1	6300	1	5985	0.95	5796	0.92	5292	0.84

Derating at different altitudes

Air circuit breaker	DMX ³ 2500, DMX ³ 4000 and DMX ³ 6300			
Altitude H (m)	< 2000	3000	4000	5000
Rated current (at 40°C) In (A)	I _n	0.98 x I _n	0.94 x I _n	0.90 x I _n
Rated voltage Ue (V)	690	600	500	440
Rated insulation voltage Ui (V)	1000	900	750	600

Minimum recommended dimension of copper busbars per pole

Frame 2500

In (A)	Fixed version		Draw-out version	
	Vertical bars (mm)	Horizontal bars (mm)	Vertical bars (mm)	Horizontal bars (mm)
630	2 x 40 x 5	2 x 40 x 5	2 x 40 x 5	2 x 40 x 5
800	2 x 50 x 5	2 x 50 x 5	2 x 50 x 5	2 x 50 x 5
1000	1 x 60 x 10 or 2 x 60 x 5	1 x 60 x 10 or 2 x 60 x 5	2 x 60 x 5	2 x 60 x 5
1250	1 x 80 x 10 or 2 x 80 x 5	1 x 80 x 10 or 2 x 80 x 5	2 x 80 x 5	2 x 80 x 5
1600	2 x 50 x 10	2 x 50 x 10	2 x 50 x 10	2 x 50 x 10
2000	3 x 50 x 10	3 x 50 x 10 or 4 x 50 x 10	3 x 50 x 10	3 x 50 x 10
2500	3 x 80 x 10	4 x 80 x 10 or 5 x 60 x 10	3 x 80 x 10	4 x 80 x 10

Frame 4000 - fixed and draw-out versions

In (A)	Vertical bars (mm)	Horizontal bars (mm)
630	1 x 40 x 10 or 2 x 40 x 5	2 x 40 x 5
800	1 x 50 x 10 or 2 x 50 x 5	2 x 50 x 5
1000	1 x 50 x 10 or 2 x 50 x 5	2 x 60 x 5
1250	2 x 60 x 5	2 x 80 x 5
1600	2 x 80 x 5	2 x 50 x 10
2000	2 x 50 x 10	2 x 60 x 10
2500	3 x 50 x 10	3 x 60 x 10
3200	3 x 100 x 10	4 x 80 x 10