

Green'up™ Premium charging stations equipment for wall mounting or fixing to the ground



0 590 52

Dimensions p. 521-522

Pack	Cat.Nos	Equipment for mounting charging stations on the wall or fixing to the ground
1	0 590 52	For plastic charging stations Pedestal for fixing plastic charging stations to the ground Option to integrate Plexo ³ boxes Cat.No 0 019 04/06/08(4 to 16 modules) for the protection devices
1	0 590 53	For metal charging stations Wall mounting kit with metal front cover
1	0 590 54	Pedestal for fixing metal charging stations to the ground Supplied with metal front cover Option to integrate protection devices on plates or rail chassis (dimensions equivalent to Atlantic box 600 x 400 mm)

Green'up™ Premium charging stations communication options



Identification via RFID badge
0 590 59 + 0 590 56



0 767 11

Pack	Cat.Nos	Communication kit
1	0 590 56	IP communication For connecting the charging station to the installation's IP network and ensuring its compatibility with the following protocols: - OCPP 1.6 and 2.0 - MODBUS RS 485 (one MODBUS address per single charging station and two MODBUS addresses per double charging station)
1	0 590 59	RFID reader RFID system (identification via RFID badge, integrated RFID encoder reader) available on metal charging stations with communication kit Cat.No 0 590 56 Supplied with 1 badge to be activated Additional badges to be ordered separately ISO format Mifare Classic technology Cat.No 0 767 11
1	0 767 11	Badge for RFID reader Mifare contactless badge ISO format (50 x 80 mm) Chip: 13.56 MHz Standard 1 kB memory
1	4 149 47	Energy management multi-support web servers Allow remote configuration, test, control and visualization, via a web browser on PCs, smartphones, web viewers, tablet computers, of data collected from: protection devices (DX ³ add-on modules with integrated measurement control unit, DPX ³ and DMX ³), EMDX ³ electricity meters and multi-function measuring units, CX ³ energy management system and Green'up charging stations for electric vehicles. Direct IP connection └ rail mounting Power supply: 9 to 28 V = with the help of a single-phase switching mode power supply Cat.No 1 467 21 (see Legrand general catalog) to be ordered separately
1	4 149 48	For 10 Modbus addresses or 10 pulse modules
1	4 149 48	For 32 Modbus addresses or 32 pulse modules
1	4 149 49	Fixing on plate For 255 Modbus addresses or 255 pulse modules

Number of modules

4

4