

Hotel equipment

shaver sockets, key card switches, key cards, chimes, buzzers



5 721 53



5 710 55



5 722 53



0 767 11

Support frame and plate selection charts **p. 594-603**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 585) and plates (p. 594-603)

Pack	Cat.Nos	Shaver sockets
		<p>Conform to BS EN 61558-2-5. IP 24 For use with European, British, American, Australian 2-pin plugs. Screwless live and neutral terminals Double wound isolating transformer Automatic self-resetting overload feature Plug insertion operates micro-switch which energises transformer To be equipped with BS 2-gang - 3-module plates (p. 594-595) For flush-mounting boxes, use BS 2-gang box depth 48 mm, US type, Italian type boxes depth 48 mm or Cat.No 0 801 55 Power supply: 230 V - 50/60 Hz. 3 modules</p> <p>230 V / 120-230 V</p> <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu ○ White - with earth connector ● Magnesium - with earth connector ● Champagne - with earth connector ● Soft Alu - with earth connector
1	5 721 55	
1	5 726 55	
1	5 726 66	
1	5 726 65	
1	5 721 53	
1	5 726 53	
1	5 727 64	
1	5 727 62	

Pack	Cat.Nos	Mechanical key card switches 230 V
		<p>For energizing a circuit by inserting a key fob Cat.No 5 722 59 or a smart card (access card for a hotel room) Example of use: hotel room power supply only when guest is present Time-delay of approx. 30 sec. after card removal To be equipped with single pole latching relay Cat.Nos 5 722 27 or 5 727 27 (p. 570)</p> <p>2 modules</p> <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu
1	5 722 30	
1	5 727 30	
1	5 700 55	
1	5 710 55	

Pack	Cat.Nos	Key card switches RFID
		<p>For energizing a circuit for example meeting room, office, hotel room... Works only with ISO type contactless key card Cat.No 0 767 11 or other ISO type 13.56 MHz key card Time-delay of approx. 30 sec. after card removal Low capacity contact 230 V - 30 VA Lighting of the slot by LED. 2 modules</p> <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu
1	5 722 53	
1	5 727 53	
1	5 727 37	
1	5 722 37	

Pack	Cat.Nos	Key cards
		<p>For mechanical key card switches Enable use of key fob switches in hotels with key locks Supplied complete with a label holder for individual hotel identification</p> <ul style="list-style-type: none"> ○ White ● Magnesium
10	5 722 59	
10	5 727 59	
		<p>For RFID key card switches MIFARE contactless badge card ISO format (50 x 80 mm) Chip: 13.56 MHz Standard 1 KB memory</p>
10	0 767 11	
		<p>Chimes 230 V - 50 Hz Consumption: 65 mA 1 melody Tone level: 73 dB at 1 m Compatible with push-button Cat.No 0 416 45</p>
1	5 722 06	
1	5 722 46	

Pack	Cat.Nos	Buzzers
		<p>230 V - 1 module</p> <ul style="list-style-type: none"> ○ White ● Magnesium
10	5 722 04	
5	5 727 04	
		<p>230 V - 2 modules</p> <ul style="list-style-type: none"> ○ White ● Magnesium
10	5 722 07	
10	5 722 47	