

# Hotel room management

UX One radio controls

January 2024

# Hotel room management

UX One room monitoring

January 2024






0 884 20



0 489 09

Products compatible with UX One thermostats

Pack	Cat.Nos	Badge reader micromodule
1	0 884 20	 <p>For connecting a conventional keycard reader to a Zigbee 3.0 installation and Green Power technologies combined, including the Proxy and Sink functions, on the ISM 2.4 GHz band (2400/2483.5 MHz), with 16 channels (11 to 26)                      Max. RF power &lt; 20 dBm/100 mW                      Range: 150 m in unobstructed space, point to point</p>
1	5 701 09	<p><b>"Do not disturb/Make up room" Arteor switch</b></p> <p>Zigbee 3.0 and Green Power technologies combined, including the Proxy and Sink functions, on the ISM 2.4 GHz band (2400/2483.5 MHz), with 16 channels (11 to 26)                      Max. RF power &lt; 20 dBm/100 mW                      Range: 150 m range in unobstructed space, point to point                      Supplied with cover plate, to be equipped with a Batibox support and a Arteor plate (p. 594)</p>  <ul style="list-style-type: none"> <li>○ White</li> <li>● Magnesium</li> <li>● Champagne</li> <li>● Soft Alu</li> </ul>
1	5 701 11	
1	5 701 12	
1	5 701 10	

Pack	Cat.Nos	Hotel gateway
1	0 489 09	 <p>For centralising all UX One thermostat data to be fed to a room monitoring interface for hotel reception                      Also used to control rooms remotely from hotel reception (scenarios, temperature)                      One hotel gateway per installation</p>