





0 489 43





Selection chart **p. 884** 

## Automatic ON/OFF

Manual adjustment of light level threshold and time delay via potentiometer

Pack	Cat.Nos	Ideal for all spaces	Pack	Cat.Nos	Ideal for outdoor and humid areas
	Retail 0 489 44 0 489 41	PIR IP 20 ceiling/flush-mounting motion sensor, 360° Range Ø8 m Recommended fixing height: 2.5 m 3-wire with neutral Light level threshold: 10 to 1275 lux Adjustable time delay: 10 s to 10 min Standby consumption: 0.75 W Optimum distance between 2 sensors: 6 m Fixes directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm	1	Retail  Cardboard 0 489 46  0 489 43	PIR IP 55 wall/surface-mounting motion sensor, 360° Range Ø8 m Recommended fixing height: 2.5 m 3-wire with neutral Light level threshold: 10 to 1275 lux Adjustable time delay: 10 s to 10 min Standby consumption: 0.75 W For direct surface-mounting on wall PIR IP 55 wall or ceiling/surface- mounting motion sensors, 360° With directional head, range Ø8 m
	Retail Cardboard 0 489 49 0 489 48		1 1	Retail Cardboard - 0 697 40 0 488 98 0 697 80	Fix directly to ceiling or wall (min. height: 1.70 m) 3-wire with neutral Light level threshold: 5 to 1275 lux Adjustable time delay: 12 s to 16 min Standby consumption: 0.9 W Optimum distance between 2 sensors: 6 m © Grey
1	Retail Cardboard 0 489 45 0 489 42	PIR IP 41 wall/surface-mounting motion sensor, 140° Range Ø8 m Recommended fixing height: 2.5 m 3-wire with neutral Light level threshold: 10 to 1275 lux Adjustable time delay: 10 s to 10 min Standby consumption: 0.75 W For direct surface-mounting on wall			



Discover and download the document motion sensors





Mosaic presence and motion sensors, p. 1176



Arteor presence and motion sensors, **p. 562** 

