

Safety boxes 125 series

for emergency applications

Automatic sensors











6 430 71

0 380 09 0 380 11

0 380 24

Pack	Cat.Nos	Break glass emergency boxes
		Polycarbonate, Class II - IK 07 Equipped with: - hinged glass door with locking option by key - 3 cable entries for CG ISO 16/20 (by top or bottom as reversible product) - 2 entries from back of product Ø20 - 2 side entries for mini-trunking 20 x 12.5 and 32 x 12.5 - 1 NC contact and 1 NO contact Breaking capacity: - 400 V √ / 4.5 A - 230 V √ / 6 A - 48 V = / 1 A - 24 V = / 1.5 A Flush-mounting option with boxes Ø85 Dim.: 125 x 125 x 71 mm (surface-mounting) IP 44 - 125 x 125 x 33 mm (flush-mounting) IP 30 Red boxes can be used for fire applications and manipulated by fire fighters Yellow boxes can be used for emergency applications and manipulated by employees
1 1 1	0 380 00 0 380 02	Mushroom head button boxes Direct actuation by smashing glass plate Equipment: - 1 mushroom head button with latching, unlocking by key No 850 - 2 long life 230 V ← LED indicators (green/red) Red box with LED Yellow box with LED Yellow box without LED Red box without LED Red box without LED
1 1 1	0 380 01	2-position boxes Equipment: - 1 mushroom head button for pressing - 1 finishing accessory for simple action release (glass break) or double action (glass break followed by pressing on mushroom head) - 2 long life 230 V LED indicators (green/red) Red box without LED Yellow box without LED Red box with LED

Pa	ck	Cat.Nos	Automatic sensors for fire detection
1		6 430 72	Optical smoke sensor Conform to EN 54-7 standard and CE CPR approved For quick detection of fire starting before flames appear Average detection area: 60 m² Supplied with its standard base
1		6 430 71	Heat sensor Conform to EN 54-5 standard and CE CPR approved Detects temperature rise with threshold of 60 °C Average detection area: 30 m ² Supplied with its standard base