

Legrand cabling system, LCS³ cat. 6


zone distribution box solution



0 337 97



0 337 63



0 517 57

Pack	Cat.Nos	Zone distribution boxes to be equipped
1	0 337 96	For distributing data in an area equipped with 1 to 24 RJ 45 sockets Centralise connections to ensure flexibility and scalability of the installation For installation in false ceilings or raised access floors The boxes connect to the patching enclosure or floor cabinet Connection to an RJ 45 socket with an RJ 45/stripped cord or to a Mosaic RJ 45 socket with copper feedthrough with an RJ 45/RJ 45 cord IP 21 - IK 07 Compliant with ISO/IEC 11 801, EN 50173 and ANSI/TIA 568 standards T568A and B marking with colour codes Technical characteristics: polycarbonate cover (PC), polypropylene base (PP), RAL 7035 To be equipped directly with RJ 45 High Density connectors
1	0 337 97	12 ports to be equipped 24 ports to be equipped

Pack	Cat.Nos	Cat. 6 High Density RJ 45 connectors
6	0 337 63	Set of 6 RJ 45 connectors
6	0 337 64	UTP
6	0 337 65	FTP STP

Pack	Cat.Nos	Cat. 6 cords - RJ 45/stripped
1	0 517 96	RJ 45/stripped - straight Plug in and out of the zone distribution boxes and connect to an LCS ³ connector of an RJ 45 socket via the stripped side Cables prepared in factory, "ready for wiring" Compliant with ISO/IEC 11801 Ed. 2.0 (2011), EN 50173-1 and EIA/TIA 568 C2 standards
1	0 517 97	Screened F/UTP, impedance 100 Ω Length 8 m
1	0 517 98	Length 15 m Length 20 m
1	0 517 57	Unscreened U/UTP, impedance 100 Ω Length 8 m
1	0 517 58	Length 15 m
1	0 517 59	Length 20 m

Pack	Cat.Nos	Cat. 6 cords - RJ 45/RJ 45
1	0 515 13	For direct connection via RJ 45 male plug to the zone distribution box and to the RJ 45 socket with copper feedthrough to ensure safe connection, plus speed and reliability of connection
1	0 515 14	Screened F/UTP, impedance 100 Ω Length 8 m
1	0 515 15	Length 15 m Length 20 m
1	0 515 10	Unscreened U/UTP, impedance 100 Ω Length 8 m
1	0 515 11	Length 15 m
1	0 515 12	Length 20 m

Pack	Cat.Nos	Cat. 6 sockets with copper feedthrough
10	0 786 22	Cat. 6 UTP - Mosaic
10	0 786 26	○ White ● Aluminium
10	0 786 23	Cat. 6 FTP - Mosaic
10	0 786 27	○ White ● Aluminium
10	5 723 31	Cat. 6 UTP - Arteor
10	5 728 31	○ White ● Magnesium
10	5 729 10	● Champagne
10	5 729 09	● Soft Alu
10	5 723 33	Cat. 6 FTP - Arteor
10	5 728 33	○ White ● Magnesium
10	5 729 12	● Champagne
10	5 729 11	● Soft Alu