

# Legrand cabling system, LCS<sup>3</sup> fiber optic

## 19" High Density fiber optic panels (1/2/4 U) and patching kits



Panel 0 321 76 equipped with support 0 321 38 and slim cassettes 0 321 69/70



0 321 38



0 321 69



0 321 70



Selection chart p. 962-965

Pack	Cat.Nos	19" High Density fiber optic panels	Pack	Cat.Nos	Preterminated MTP <sup>(1)</sup> High Density cassettes (MPO compatible) (continued)
		<b>Panels to be equipped with cassettes</b>			<b>Ultra slim cassettes</b>
		Equipped with Quick-Fix system for automatic (screwless) mounting on enclosure or cabinet uprights	1	0 321 38	Support for High Density slim cassettes
		To be equipped directly with a maximum of 4 automatically removable cassettes or 4 supports for slim cassettes Cat. No 0 321 38 per U			Takes up to 2 High Density slim cassettes
		Maximum capacity per U: 48 fibers in SC version, 24 fibers in ST version or 96 fibers in LC version	1	0 321 69	Cat.Nos 0 321 68/69/70 and up to 2 blanking cassettes
		2U and 4U versions equipped with door and cord management at the front, and with cable management at the back	1	0 321 68	Cat.No 0 321 39 or 1 cassette + 1 blanking cassette
1	0 321 75	1 U height, depth 182 mm	1	0 321 70	Possibility to mix slim single-mode and multimode cassettes on the same support
1	0 321 76	2 U height, depth 393 mm	1	0 321 39	Slim multimode OM4 cassette (50/125 µm)
1	0 321 77	4 U height, depth 393 mm			12 LC fibers, Universal polarity
		<b>Accessories for panels</b>			Slim multimode OM3 cassette (50/125 µm)
1	0 321 78	Front cord management kit for 1 U panel	1	0 321 70	12 LC fibers, Universal polarity
		Fits on 1 U modular panel Cat.No 0 321 75	1	0 321 39	Slim single-mode OS2 cassette (9/125 µm)
		2 side cord guides and front door with integrated marking to ensure correct front and side cord management			12 LC fibers, Universal polarity
		Cord holder to be mounted on cassette to make it easier to pass cords through the side	1	0 321 39	Slim blanking module to be mounted (x2) on support
1	0 321 46	Rear cable management accessory			Cat.No 0 321 38 to fill gaps in the panel
1	0 321 28	Accessory for receipt of a fan-out			
		To be clipped onto the back of the drawer			
1	0 321 22	Enables the entry of preterminated links			
4	0 321 26	Copper cable management accessory			
		Set of 4 cord holders			
1	0 321 05	To be mounted on any cassette to make it easier to pass cords through the side			
		Rear accessory for fixing 4 cable glands			
		<b>Ultra preterminated MTP<sup>(1)</sup> High Density cassettes (MPO compatible)</b>			<b>Core pre-equipped cassettes</b>
		For installation in modular panels			For installation in modular panels
		Cat. Nos 0 321 75/76/77 and in Zero-U kit			Cat. Nos 0 321 75/76/77 and Zero-U kit Cat.No 0 321 03
		Cat. No 0 321 03			Pre-equipped cassettes with fitted fiber optic block + sets of 6 or 12 OM3 pigtailed
		Slim cassettes to be installed with support			Sliding cassettes which can be removed automatically by simply pressing them, simplifying installation and maintenance
		Cat. No 0 321 38			Removable from the front
		Sliding cassettes which can be removed automatically by simply pressing them, simplifying installation and maintenance			
		Removable from the front and back			<b>Pre-equipped cassettes for multimode installation (50/125 µm)</b>
		Multimode - Insertion Loss Max/Random <sup>(2)</sup> : 0.55 dB	1	0 321 80	Equipped with 1 SC duplex block for 6 fibers
		Single-mode - Insertion Loss Max/Random <sup>(2)</sup> : 0.6 dB	1	0 321 81	Equipped with 1 LC duplex block for 6 fibers
		Prewired, equipped at the rear with one or two male MTP <sup>(1)</sup> connectors with 12 fibers	1	0 321 82	Equipped with 1 SC duplex block for 12 fibers
		LC or SC connectors at the front	1	0 321 83	Equipped with 1 LC duplex block for 12 fibers
		<b>Ultra cassettes</b>			<b>Pre-equipped cassettes for single-mode installation (9/125 µm)</b>
1	0 321 42	Multimode OM4 cassette (50/125 µm)	1	0 321 84	Equipped with 1 SC duplex block for 6 fibers
		24 LC fibers, A/C polarity	1	0 321 85	Equipped with 1 LC duplex block for 6 fibers
1	0 321 48	Multimode OM4 cassette (50/125 µm)	1	0 321 86	Equipped with 1 SC duplex block for 12 fibers
		12 LC fibers, A/C polarity	1	0 321 87	Equipped with 1 LC duplex block for 12 fibers
1	0 321 43	Multimode OM4 cassette (50/125 µm)			<b>Cassettes to be equipped and blanking plate</b>
		12 SC fibers, A/C polarity			For installation in modular panels
1	0 321 44	Single-mode OS2 cassette (9/125 µm)			Cat. Nos 0 321 75/76/77 and Zero-U kit Cat. No 0 321 03
		24 LC fibers, A/C polarity			Sliding cassettes which can be removed automatically by simply pressing them, simplifying installation and maintenance
1	0 321 49	Single-mode OS2 cassette (9/125 µm)			Removable from the front
		12 LC fibers, A/C polarity			
1	0 321 45	Single-mode OS2 cassette (9/125 µm)	1	0 321 41	<b>Fiber optic splice cassette</b>
		12 SC fibers, A/C polarity			Takes any modular fiber optic block
			1	0 337 57	<b>Blanking cassette</b>
					To be used to fill gaps in the panel
			1	0 337 55	<b>Copper cassette to be equipped</b>
					Takes six cat. 5e, 6 and 6 <sub>A</sub> copper connectors
					<b>Patching kits</b>
					<b>1 U to 4 U patching kit</b>
			1	0 321 89	Compatible with all LCS <sup>3</sup> fiber optic and copper 19" panels
					Supplied with top protection, cable guides and specific accessories for installation on cable trays, wire meshed cable trays (Cablofil) and cabinets
					<b>Zero-U patching kit</b>
			1	0 321 03	To bring few fiber optic or copper connections outside 19" panels
					Takes 1 cassette (fiber optic preterminated cassettes, pre equipped cassettes, fiber optic splice cassette or RJ 45 copper cassette)
					Supplied with a comprehensive range of accessories for fixing in or outside enclosures (raised access floors, cable trays, walls, ceiling)

1: MTP is a registered trademark of US Conec Ltd  
2: When mated with the same Legrand range (Ultra & Core) trunks and patch cords