

Incara™ Multilink - German standard

for offices and meeting rooms



Technical characteristics p. 1107

For integration in furniture (horizontal flush-mounting, remote terminal block) or a dry partition (vertical flush-mounting, terminal block in the casing)
 Max. power: 3680 W at 230 V~
 2P+E sockets: 16 A 250 V~ 50/60 Hz, equipped with safety shutters, conforming to standard IEC 60884-1
 USB chargers: 110-240 V~ 50/60 Hz power supply, conforming to standard IEC 62368-1
 RJ 45 and HDMI sockets: feedthrough sockets

Incara Multilink for integration in furniture

Pack	Cat.Nos	Description
		Extruded aluminium. Equipped with Mosaic functions With 2 m cord and 2P+E plug Compatible desk thickness 10-40 mm
1	6 547 89	4 modules Composition: 1 x 2P+E socket + 1 x 15 W USB Type-A + Type-C charger
1	6 547 79	● Black metal
1	6 547 85	○ White
1	6 547 85	● Black
1	6 547 93	6 modules with 30 W Power Delivery charger Composition: 2 x 2P+E sockets + 1 x USB Type-C 30 W Power Delivery charger
1	6 547 90	● Black metal
1	6 547 80	○ White
1	6 547 86	● Black
1	6 547 91	8 modules Composition: 2 x 2P+E sockets + 1 x 15 W USB Type-A + Type-C charger + 1 x RJ 45 cat. 6 UTP socket + 1 HDMI socket
1	6 547 81	● Black metal
1	6 547 81	○ White
1	6 547 87	● Black

Incara Multilink for integration in a partition

Pack	Cat.Nos	Description
		Compatible partition thickness: 10-25 mm
1	6 548 62	8 modules Composition: 3 x 2P+E sockets + 1 x 15 W USB Type-A + Type-C charger
1	6 548 63	○ White
1	6 548 63	12 modules Composition: 3 x 2P+E sockets + 1 x 15 W USB Type-A + Type-C charger + 3 x RJ 45 cat. 6 UTP sockets, 1 module
1	6 548 63	○ White
1	6 548 65	16 modules 2 vertical rows of 8 modules Composition: + 3 x 2P+E sockets + 1 x 15 W USB Type-A + Type-C charger + 4 x RJ 45 cat. 6 UTP sockets, 2 modules
1	6 548 65	○ White

Other configurations available on request:
 HDMI cable reel, RJ 45 cable reel, etc.

Incara™ Flip-up - German standard

for meeting rooms



Technical characteristics p. 1108

For flush-mounting in furniture, compatible table thickness 15 to 40 mm
 Ready to use
 Max. power: 3680 W at 230 V~
 2P+E sockets: 16 A 250 V~ 50/60 Hz, equipped with safety shutters, conforming to standard IEC 60884-1
 USB chargers: 110-240 V~ 50/60 Hz power supply, conforming to standard IEC 62368-1
 Feedthrough RJ 45 and HDMI sockets
 Snap-on fixing via retractable clamps

Incara Flip-up multi-outlets for flush-mounting

Pack	Cat.Nos	Description
		With 2 m cord and 2P+E plug Black metal cable grommet shutter
1	6 548 54	8 power modules Composition: - 3 x 2P+E sockets - 1 x 15 W USB Type-A + Type-C charger
1	6 548 55	● Metal
1	6 548 56	8 power and data modules Composition: - 2 x 2P+E sockets - 1 x RJ 45 cat. 6 UTP feedthrough socket, 1 module - 1 x feedthrough HDMI socket - 1 x 15 W USB Type-A + Type-C charger
1	6 548 56	● Metal
1	6 548 57	12 power modules Composition: - 5 x 2P+E sockets - 1 x 15 W USB Type-A + Type-C charger
1	6 548 57	● Metal
1	6 548 57	12 power and data modules Composition: - 3 x 2P+E sockets - 3 x RJ 45 cat. 6 UTP feedthrough sockets, 1 module - 1 x feedthrough HDMI socket - 1 x 15 W USB Type-A + Type-C charger
1	6 548 57	● Metal

Other configurations, socket standards and finishes available on request or via the pCon software