


MS double sided busbar

tap-offs and accessories



Tap-offs can be supplied pre-wired and fitted with protective devices

Contact us on +44 (0) 345 600 6266



Dimensions and technical information p. 25-26

Tap-off boxes can be used to connect and energise one and three phase loads up to 63 A. Tap-offs can be inserted and removed when the busbar is energised and when the fixture is under load, up to a capacity 32 A. Compliant with IEC 60695-2-10 with V1 self-extinguishing degree (UL 94) Standard IP 55 degree of protection

Pack	Cat. Nos.	Tap-off boxes IP 55
		Energy withstand 400·10 ³ A ² S Totally insulated tap-off box Max. cable size 25 mm ² Max. power losses 10 W
1	51515071	Empty tap-off box with DIN (4 mod.) Rating (A) Weight (kg) 32 0·68
1	51515072	Tap-off box for (4 mod.) DIN Rating (A) Weight (kg) 32 0·73
1	51515073	Max. power losses 16 W Empty tap-off box (8 mod.) Rating (A) Weight (kg) 32 0·93
1	51515074	Tap-off box (4 mod) DIN (long version) Rating (A) Weight (kg) 32 0·96
1	51515075	Tap-off box (8 mod) DIN (long version) Rating (A) Weight (kg) 32 0·99

Pack	Cat. Nos.	Tap-off boxes with isolating device on the cover
1	51515051	Tap-off box with CH10 fuseholder (10·3 x 38) 10·3 x 38 fuses not included Rating (A) Weight (kg) 16 0·908
1	51515052	Tap-off box with CH14 fuseholder (14 x 51) 14 x 51 fuses not included Rating (A) Weight (kg) 50 0·908
1	51515057	63 A tap-off boxes Energy withstand 400·10 ³ A ² S Max power losses 20W Tap-off box with transparent cover Weight 1·1 kg
1	51515056	Tap-off box with transparent cover and hinged door (up to 4 mod.) Weight 1·2 kg
1	51515067	Tap-off box with hinged door (up to 7 mod.) Weight 1·1 kg
1	51515058	Tap-off box with hinged door (up to 16 mod.) Energy withstand 400·10 ³ A ² S Max power losses 20W Weight 2·5 kg

Pack	Cat. Nos.	Accessories
1	51501351	End cover IP 55 End covers are fitted to the last length in each run to maintain IP 55 protection Weight 0·57 kg
1	51500161	Joint cover IP 55 One for each joint Weight 0·788 kg
1	51500160	Tap-off outlet cover IP 55 6 per 3 m straight length Weight 0·061 kg
1	51002002	Suspension bracket Universal fixing brackets enable trunking to be either suspended or wall mounted 1 per 2 m Weight 0·1 kg