

BREAK OUT ASSEMBLY, 220 x 100 mm AND 300 x 100 mm DUCT

Part number: TC1279-330A



1. USE / APPLICATION

The break out assembly is used to provide a safe, exit for optical fibre cord/s to equipment, at any point in 220 or 300 mm ducting system. It is normally used to provide a break out in existing duct systems, and clips straight into a cut out, 2 cuts wide, provided by the cut out tool (Part No: TC1279-231KIT). When used as described, it provides a 220 mm outlet; to which any standard 220 mm part can be fitted (using either: the standard joiner (Part No: TC1279-25) or the slotless joiner (Part No: TC1279-250A). A standard joiner is supplied. It can also be used with vertical duct to feed patch cords down to a rack. (Used as a Trumpet Outlet).

2. BENEFITS & FEATURES

- Lid to suit included (Part No: TC1279-332)
- Fits directly to the cut out, 2 cuts wide, provided by the standard tool (Part No: TC1279-231KIT).
- Connects to duct using either: the standard joiner (Part No: TC1279-25); which is supplied; or the slotless joiner (Part No: TC1279-250A); which is available separately
- Tough, fire retardant material
- Purchase by the unit

3. TECHNICAL ATTRIBUTES

Dimensions	325 mm (W) x 105 mm (H) x 111 mm (D)
Weight	182 grams (Lid = 46 grams)
Materials	Fire retardant plastic, Halogen free, UL94-VO rated