


128, av. du Maréchal-de-Lattre-de-Tassigny - 87045 LIMOGES Cedex Tel.: 33(0)5 55 06 87 87 - Fax: 33(0)5 55 06 88 88 www.legrand.com

Mosaic[™] Connected 2-gang ON/OFF wireless control for lighting and sockets



1. USE

Wireless control for 2 ON/OFF light functions or connected socket. Controls micromodule products, connected sockets and connected dimmer switches.

Can be used as a two-way switch or to control a lighting group.


Fixes directly on the wall or screws onto a flush-mounting box. Multi-gang versions can be combined with other wiring accessories.
Fits on a piece of furniture (movable).

Can control up to 20 micromodules, connected sockets, connected dimmer switches.

2. RANGE


| Description | White |
|---|------------|
| 2-gang wireless lighting and socket control for an ON/OFF, dimmer, centralisa- tion function. Supplied with battery. With LED indicator (configuration) and RESET button (hidden) used to return to factory settings. Repositionable self-adhesive fixings supplied. To be equipped with plate. | 0 777 24LA |

3. DIMENSIONS (mm)



| Α | В | с |
|----|----|----|
| 74 | 74 | 12 |

4. OPERATION



Short press: ON/OFF Long press: Dimming +

LED indicators: - useful during installation - when pressed, burst flash red if the battery power is low

Short press: ON/OFF Long press: Dimming -



RESET button used to return to factory settings

5. TECHNICAL CHARACTERISTICS

5.1 Mechanical characteristics

Protection against impacts: IK 02 Protection against solid bodies/liquids: IP 20 without plate or rocker plate IP 40 for assembled product

■ 5.2 Material characteristics

Rocker plate: PC Colour: white RAL 9003 Mechanism casing with grid: Fibreglass-reinforced (10 %) PC

Halogen-free UV-resistant

Self-extinguishing: 650°C/30 s

■ 5.3 Electrical characteristics Powered by a CR2032 - 3 V lithium battery (supplied)

Battery life: 8 years for 10 activations a day

ZigBee radio technology

Frequency: 2.4 GHz to 2.4835 GHz Power level: < 100 mW

■ 5.4 Climate characteristics

Usage temperature: +5°C to +45°C Storage temperature: 0°C to +45°C

6. CARE

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistant to the following products: Hexane (EN 60669-1), methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

Caution: Always test before using special cleaning products.

 $\overline{\mathbb{N}}$

Take care to recycle the battery appropriately

7. ACCESSORIES

0 648 71: Repositionable adhesive for wireless control (supplied)

8. STANDARDS AND APPROVALS

The undersigned, LEGRAND, declares that the radio-electric equipment type (0 777 24LA) complies with directive 2014/53/EU. The full text of the EU declaration of conformity is available on the following website: **www.legrandoc.com**