


## Cat. No(s): 0 677 61A/62A/63A



## 1. USE

2-speed exhaust fan wireless switch to control exhaust fan micromodule (Cat. No 0 677 66).

• Fixes directly on the wall or screws onto a flush-mounting box. Multigang versions can be combined with other wiring accessories.


Fits on a furniture (movable).

Can control up to 20 exhaust fan micromodules.


### 2. RANGE

Description	White	Titane	Graphite
Connected wireless control for 2-speed exhaust fan. Supplied with battery. With LED indicator (configuration) and RESET button (hidden) used to return to factory settings. Repositionable self-adhesive fixings supplied. To be equipped with plate.	0 677 61A	0 677 62A	0 677 63A

## 3. DIMENSIONS (mm)



Α	В	с
74	74	13



**4. FUNCTION** 

#### LED indicator - - useful during 'installation - when pressed, burst flash red if the battery power is low

– High

Low



RESET button used to return to factory mode.

## **5. TECHNICAL CHARACTERISTICS**

### 5.1 Mechanical chacaracteristics

Protection against impacts: IK 02 Protection against solid bodies/liquids: IP 20 without plate and rocker plate IP 40 for assembled product

### ■ 5.2 Material characteristics

Mechanism casing with grid: Fibreglass-reinforced (10%) PC

Colour	White	Titane	Graphite
Rocker plate	ABS	Painted ABS	Painted ABS
		•	

Halogen-free UV-resistant

Self-extinguishing: 650°C/30 s

## 5.3 Electrical characteristics

Powered by a CR2032 - 3 V lithium battery (supplied) Battery life: 8 years for 10 activations a day Frequency band: 2.4 to 2.44835 GHz Power level: < 100 mW

### 5.4 Climate characteristics

Usage temperature:  $+5^{\circ}C$  to  $+45^{\circ}C$ Storage temperature:  $0^{\circ}C$  to  $+45^{\circ}C$ 

# 6. CARE

∕₹∖

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene. Resistant to the following products: Hexane (EN 60669-1), methylated

spirit, soapy water, diluted ammonia, bleach diluted to 10%, windowcleaning products, pre-impregnated wipes.

**Caution:** Always test before using special cleaning products.

Take care to recycle the battery appropriately

## 7. ACCESSORIES

0 648 71: Repositionable adhesives for wireless control (supplied)

### 8. STANDARDS AND APPROVALS

The undersigned, LEGRAND, declares that the radio-electric equipment type (0 677 61A/62A/63A) complies with directive 2014/53/EU. The full text of the EU declaration of conformity is available on the following website: **www.legrandoc.com** 

Compliant with installation and manufacturing standards. See e.catalogue.