


# Arteor™ with Netatmo - British Standard Connected Wake up/Sleep wireless control

Cat. Nos: 5 746 51/52/53/54



## 1. USE


Used to control wake up/sleep scenes involving lights, curtains/roller shutters and connected socket outlets. Requires the prior installation of a starter pack for connected installation or a Control module "with Netatmo".

- Fixes directly on the wall or screws onto a flush-mounting box. Multi-gang versions can be combinated with other wiring accessories.
- Fits on a piece of furniture (movable).

# 2. RANGE

Description	White	Magnesium	Soft Alu	Champagne
Wake up/Sleep wireless control, with battery. Supplied with a secable support frame and a rocker plate. Equipped with an LED indicator (configuration) and a RESET button (hidden) used to return to factory settings. Repositionable self-adhesive fixings (supplied).	5 746 51	5 746 52	5 746 53	5 746 54


# 3. DIMENSIONS





Α	В	B'	С
82	116.5	82	12

# 4. OPERATION




Wake up scenario when pressed at the top: By default, switches on the connected sockets Can be customised with the Home + Control app

LED indicator:

useful during installation
 when pressed, burst flashes red if the battery power is low

Sleep scenario when pressed at the bottom: By default, switches off all the lights in the installation Can be customised with the Home + Control app



RESET button used to return to factory mode

# Arteor™ with Netatmo - British Standard Connected Wake up/Sleep wireless control

## **5. TECHNICAL CHARACTERISTICS**

#### ■ 5.1 Mechanical characteristics

Protection against impacts: IK 02 Protection against solid bodies/liquids: IP 20

## ■ 5.2 Material characteristics

Rocker plate: ABS

Mechanism with grid: Fibreglass-reinforced (20%) PC

Halogen-free

UV resistant

Self-extinguishing: 650°C/30 s

### ■ 5.3 Electrical characteristics

Powered by a CR2032 - 3 V lithium battery (supplied) Battery life: 8 years for 10 activations a day

#### ZigBee radio technology

Frequency bands: 2.4 GHz to 2.4835 GHz

Power level: < 100 mW

#### ■ 5.4 Climate characteristics

Usage temperature: +5°C to +35°C Storage temperature: 0°C to +45°C

## 6. CARE

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistant to the following products:

Hexane, methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

**Caution:** Always test before using special cleaning products.



Take care to recycle the battery appropriately

## 7. STANDARDS AND APPROVALS

The undersigned, LEGRAND, declares that the radio-electric equipment type (5 746 51/52/53/54) complies with directive 2014/53/EU. The full text of the EU declaration of conformity is available on the following website: www.legrandoc.com

Cat. Nos: 5 746 51/52/53/54