

Céliane™ Contactless switch for light Cat. No(s): 0 670 40



1. USE

Switches the light on or off by simply passing a hand in front of the switch Detection distance: approximately 6 cm

Can be used as:


- Simple switch: wired without neutral
- 2-way switch: must be wired with neutral
- Master/slave: must be wired with neutral, 3 slaves max.
- NO pushbutton: must be wired with neutral, for controlling a relay, latching relay or "with Netatmo" micromodule.

For installation in any type of box.

2. RANGE

Description	Cat. No
Contactless switch for light. With illuminated indicator, active by default (can be deactivated). To be equipped with support frame, rocker plate and finishing plate.	0 670 40

3. DIMENSIONS (mm)



4. CONNECTION

Terminal type: with screws Terminal capacity: 2 x 2.5 mm² Stripping length: 8 mm

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Impact tests: IK 04

Protection against solid bodies and liquids: IP 41

■ 5.2 Material characteristics

Mechanism casing: PC

Halogen-free

Self-extinguishing:

 850°C/30 s for insulating components holding live parts in place. 650°C/30 s for other insulating components.

■ 5.3 Electrical characteristics

Voltage: 110-240 V~ Power: 200 W Frequency: 50/60 Hz

■ 5.4 Climate characteristics

Storage temperature: -10°C to +70°C Usage temperature: -5°C to +35°C

6. CARE

Cover plates:

0 682 27: White RAL 9003 ABS + antimicrobial* surface treatment

0 683 27 : Titane painted ABS 0 679 48 : Graphite painted ABS

*This product is made of silver-ion based antimicrobial material.

This technology eliminates bacteria, fungi and viruses without creating any immunisation or resistance effects (physical, rather than chemical, destruction).

Particularly suitables for healthcare establishments (hospitals, clinics, nursing homes, laboratories, waiting rooms, etc.) and more generally for areas subject to hygiene restrictions (industrial, shared and restaurant kitchens, waste, etc).

This product offers an additional way of ensuring the non-proliferation of bacteria, fungi and viruses without interfering with cleaning protocols.

7. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards. See e.catalogue.

*Contains silver ions that limit the development of bacteria on the surface.