

**MODBUS TABLE ORGANIZATION**

Starting Address of the Group Registers (Dec)	Starting Address of the Group Registers (Hex)	System Version (Release)	System Version (Build)	Group Name (Text)	Group Code (Hex)	Group Complexity (Hex)	Group Version (Hex)	Object Code
18432	4800	01	16	Breaker Command	62 01	10	01 00	
18432	4800	01	16	Breaker Command Configuration	62 01	10	01 00	

**MODBUS PROTOCOL DETAILS**

Function Code (Dec)	Exception Codes (Dec)	Data Encoding
2 (Read Discrete Inputs)	1, 2, 3	"Big Endian" (most significant byte first)
1 (Read Coils)	1, 2, 3	"Big Endian" (most significant byte first)
5/15 (Write Single/Multiple Coils)	1, 2, 3	"Big Endian" (most significant byte first)
4 (Read Input Registers)	1, 2, 3	"Big Endian" (most significant byte first)
3 (Read Holding register)	1, 2, 3	"Big Endian" (most significant byte first)
6/16 (Write Single/Multiple Holding register)	1, 2, 3	"Big Endian" (most significant byte first)

**MODBUS OVER SERIAL DETAILS**

Physical Layer	Transmission Modes	Device Addressing	Baud Rates (bit/s)	Data Bits	Data bits transmission sequence	Parity	Stop Bits
standard EIA/TIA 485 (RS-485) two-wire configuration	RTU	1÷247	programmable (1200, 2400, 4800, 9600, 19200, 38400)	8	Least significant bit first	NONE	1

**MASTER/SLAVE COMMUNICATION TIMING**

Timer Description	Timer Value (msec)
Inter-character time-out	< 1,5 character times
Response delay (from master request)	-
Delay Time (between two master transmissions)	-

REFER ALSO TO:

[www.modbus.org](http://www.modbus.org)

- MODBUS over serial line specification and implementation guide V1.02
- MODBUS APPLICATION PROTOCOL SPECIFICATION V1.1b

NOTE:

File and printed copies of this document are not subject to document change control.

Register Number	Register Address (Dec)	Register Address (Hex)	Dimension [bit]	Description	Note	Read Function Codes (Dec)	Data Storing
(no DISCRETE INPUTS availables)							

Register Number	Register Address (Dec)	Register Address (Hex)	Dimension [bit]	Description	Note	Read Function Codes (Dec)	Write Function Codes (Dec)	Data Storing
<b>18433</b>	<b>18432</b>	<b>4800</b>	<b>2</b>	<b>Breaker Command</b>				
18433	18432	4800	1	Open		1	5,15	
18434	18433	4801	1	Close		1	5,15	

Register Number	Register Address (Dec)	Register Address (Hex)	Dimension [word]	Bit Position	Description	Type	Scale	Unit	Range	Note	Read Function Code (Dec)	Data Storing
(no INPUT REGISTERS available)												

Register Number	Register Address (Dec)	Register Address (Hex)	Dimension [word]	Bit Position	Description	Type	Scale	Unit	Range	Note	Read Function Codes (Dec)	Write Function Codes (Dec)	Data Storing
<b>18433</b>	<b>18432</b>	<b>4800</b>	<b>5</b>		<b>Breaker Command Configuration</b>								
18433	18432	4800	1		Command Open configuration		-	-		See Note 3	3	6,16	
18434	18433	4801	1		Activation Time Open Command		0,1	sec			3	6,16	
18435	18434	4802	1		Delay activation Time Open Command		0,1	sec			3	6,16	
18436	18435	4803	1		Command Close configuration		-	-		See Note 3	3	6,16	
18437	18436	4804	1		Activation Time Close Command		0,1	sec			3	6,16	
18438	18437	4805	1		Delay activation Time Open Command		0,1	sec			3	6,16	

**Note 3**

bit0:

"0": Normally Open (NO)

"1": Normally Close (NC)

bit1|2:

"00": Impulsive command

"01": toggle command

"10": maintained command

bit3:

"0": Independent outputs

"1": Interlocked outputs

bit4÷15: not used