


Niloe™ TV/R sockets for cable networks

Cat. Nos: 6 645 82 - 6 646 82




1. USE


For receiving TV and radio signals on the 5-862 MHz terrestrial frequency band only Used for installation maintenance Class A shielding - Star wiring Recommended cable 17/19 VATC Single cable entry

2. RANGE

Item	Col	No. of modules	
	White	lvory	
TV/R socket for cable networks	6 645 82	6 646 82	2


3. DIMENSIONS (mm)






Cat. Nos	Α	В	C	D
6 645 82 - 6 646 82	75.8	75.8	31	12


4. CONNECTION





5. WIRING PRECAUTIONS

Ø < 7 mm 10 mm 8 mm 0 > 7 mm 17/19 VATC A 20 mm 2 mm



Connection from the rear of the socket reduces deformation of the coaxial cable, thus avoiding the risk of impedance loss and impaired performance.

6. TECHNICAL CHARACTERISTICS

■ 6.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 21 Protection against impact: IK 04 Cable strength 120 N: IEC 61169-24

■ 6.2 Material characteristics

Material: - Cover plate: ABS

- Zero halogen
- UV resistant
- Motor: Casing: Zamac
 - Cover: Zamac
 - Pin: Bronze
 - Screws: Steel

■ 6.3 Electrical characteristics

- Male connector Ø 9.52 mm (TV)
- Female connector (radio)
- Characteristic impedance: 75 ohm

Class A shielding efficiency (class A shielding is necessary to prevent interference from 3G and 4G phone signals, as these undesirable signals can cause pixellation of on-screen images or distort soundtracks)

- Frequency bands: TV: 5-68/120-862 MHz

R: 87.5-108 MHz

- Insulation resistance: IEC 61169-24

■ 6.4 Climate characteristics

Storage and operating temperature: -5 °C to +35 °C

7. CLEANING

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistant to the following products: hexane (EN 60669-1), methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

Caution: Always test before using special cleaning products.


8. STANDARDS AND APPROVALS


- EN 50083-2
- Approved by Interkabel and Telenet for Belgium
- Class A certificate



Cat. Nos: 6 645 82 - 6 646 82

9. PERFORMANCE





Data sheet: S000092713EN/00