

EBDSPIR-AD-LV | 1-10V analogue dimming, compact, IP40, ceiling, flush mounted, PIR, presence/absence detector, low voltage






Key Product Features:

- Low profile design
- Low voltage
- Self contained unit
- Pluggable
- Range up to 7m at 2.8m mounting height
- Infrared programmable
- Full programmable via our UHS5 or UNLCDHS infrared handsets
- User handset available to control on/off, lux levels and preset scenes
- Flush or surface mounted with DBB accessory
- 5 year warranty

Key Functions:


- Switching/Dimming with Lux Level Sensing
- Step-down illuminance
- Maintained Illuminance (daylight linking or daylight harvesting)
- Suitable for all lighting types
- Two channel flexibility
- Scene setting and recall
- Lamp burn-in

Detection pattern



high (sensitivity low

Dimensions (mm)



Technical Data

Part Code	EBDSPIR-AD-LV
Control method	1–10V analogue dimming
Weight	0.150kg
Supply voltage AC	10-26.5 VAC
Supply voltage DC	11.5-36 VDC
Supply frequency	50Hz
Power consumption parasitic	270mW
Terminal capacity	2.5mm ²
Max load	10A
Number of drivers/ballasts	Up to 10
Working temperature range	-10 to 50°C
Humidity	5 to 95% non-condensing
Material (casing)	Flame retardant ABS and PC/ABS
Insulation class	2
IP rating	40
Compliance (€	EMC-2014/30/EU LVD-2014/35/EU

Accessories and Associated Products

Part Number	Description
UHS5	Compact, programming/ commissioning handset
UHS7	Compact, user handset
UNLCDHS	Professional, programming/ commissioning LCD handset
EBD-ENCIP1	Pre-drilled 64mm hole detector adapter enclosure
EXD-HSC	Extended wiring housing
EBDSPIR-MS	Masking shields for EBDSPIR range
DBB	Surface mount back box for 76mm diameter detectors and light level controls
DBB-EXT	Surface mount back box extender for 76mm diameter detectors and light level controls



CP Electronics A Business unit of Legrand Electric Limited, Brent Crescent, London NW10 7XR, UK t. +44 (0)333 900 0671 info@cpelectronics.co.uk

www.cpelectronics.co.uk

connect with us 🔰 in 📑 🔛





Important notice:

This device should be installed by a qualified electrician in accordance with the latest edition of the IEE Wiring Regulations and the applicable Building Regulations.

 $\label{eq:decomposition} \mbox{Due to our policy of continual product improvement}$ CP Electronics reserves the right to alter the specification of this product without prior notice.



